# **Dynamic Braking Resistors**



#### INFORMATION

### **Vishay Milwaukee Series:**

GRE1, GRES: http://www.vishay.com/doc?31833

## **What They Do**

· When a load is being decelerated, the motor acts as a generator, converting kinetic energy of the load to electrical energy. The dynamic braking circuit converts this electrical energy into heat to slow the load, through the use of dynamic braking resistors. Braking resistors ensure proper motor operation, allowing heavy loads to stop quickly and protect the drive from damage.

## **Electrical Capabilities**

- Full range of power and resistance capabilities
- Optional terminal blocks and thermal switches
- Grid and wirewound resistor technologies

#### **Key Parameters**

- IP00-, IP20-, and IP23-rated mounting configurations
- Stainless steel resistor elements offer high thermal capacity

#### **Application Specifics**


- Found in the oil and gas, industrial, and renewable energy markets
- Used with both AC variable-frequency drives and DC drive applications such as: overhead cranes, port cranes, industrial factories (automated production lines), and large ships


# **Examples of Various Form Factors**

(Not to scale with each other)









# **How Can We Help**

- What are the requirements as specified by the drive manufacturer (ohms, watts, duty cycle)?
- Do you have any special requirements for the resistor assembly and mounting configuration?
- If using an IP-rated enclosure, do you require a terminal block, thermal switch, lifting eyes, etc.?

#### VISHAY INTERTECHNOLOGY, INC.



SALES INFORMATION











# **Dynamic Braking Resistors**



# COMPLETE FORM TO RECEIVE A QUOTATION

VISHAY INTERTECHNOLOGY, INC.

Nominal ohms:				
(Typical tolerance is 10 %. If lower is required please include that info)  Is there an absolute minimum ohms requirement?:				
(Motor manufacturers will often provide	•			
Is there an absolute maximur (Some applications require a minimum	•			
Average continuous duty pov	er:			
IF cycled a	oplication:			
Peak power:(Average of the on time)				
Seconds ON:				
Seconds O	FF:			
DC bus voltage:				
Enclosure Info				
Type: Indoor (IP20)	☐ Outdoor (IP23)	☐ Frames (IP00)		
Finish: Mill galvanized	☐ Stainless steel	☐ Other		
Other considerations/ad				
Space limitations:				
Thermal switch kit:(NC snap-action thermal switch wired to a terminal block or no switch)				



1-888-616-6666



vishaymilwaukeeresistor@vishay.com









SALES INFORMATION

