

High Voltage Generator 60KV/100 μ A


FEATURES

- Powder or flock coating applications
- Compact dimensions
- Low weight
- High reliability



GENERAL SPECIFICATIONS	
Part-No.	BG 1972-6100-010
Control unit	1972-6123-020
Type of construction	tubular
Supply voltage	1 to 24V
Input current	0.4A
Output voltage	- 60kV
Output current	- 100 μ A
Output power	6W maximum
Dimensions	\varnothing 27mm x 110mm
Weight	160g

CHARACTERISTIC





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.