# Metallized Polyester Film Capacitors
# MKT Radial Potted Types



## FEATURES

- Material categorization:
  for definitions of compliance please see www.vishay.com/doc?99912

Pb-free
RoHS COMPLIANT
HALOGEN FREE
GREEN (5-2008)

## APPLICATIONS

Blocking, bypassing, filtering and timing, high frequency coupling and decoupling for fast digital and analog ICs, interference suppression in low voltage applications.

| QUICK REFERENCE DATA | |
|---|---|
| Capacitance range | 1 nF to 1.0 µF (E12 series) |
| Capacitance tolerance | ± 20 % (M), ± 10 % (K), ± 5 % (J) |
| Climatic testing class according to IEC 60068-1 | 55/100/56 for rated voltage 63 V<br>55/105/56 for rated voltage > 63 V |
| Reference specifications | IEC 60384-2 |
| Dielectric | Polyester film |
| Electrodes | Metallized |
| Construction | Mono construction |
| Encapsulation | Flame retardant plastic case and epoxy resin sealed (UL-class 94 V-0) |
| Leads | Tinned wire |
| Marking | Manufacturer's logo/type/C-value/rated voltage/tolerance/date of manufacture |
| Rated DC voltage | 63 $V_{DC}$, 100 $V_{DC}$, 250 $V_{DC}$, 400 $V_{DC}$ |
| Rated AC voltage | 40 $V_{AC}$, 63 $V_{AC}$, 160 $V_{AC}$, 200 $V_{AC}$ |
| Rated temperature | 85 °C |
| Maximum application temperature | 100 °C for rated voltage 63 V<br>105 °C for rated voltage > 63 V |
| Performance grade | 1 (long life) |

**Note**

- For more detailed data and test requirements, contact dc-film@vishay.com

## DIMENSIONS in millimeters





For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## COMPOSITION OF CATALOG NUMBER

| MULTIPLIER (nF) | |
|---|---|
| 0.1 | 2 |
| 1 | 3 |
| 10 | 4 |
| 100 | 5 |

| CAPACITANCE (numerically) |
|---|
| Example: |
| 468 = 680 nF |

| MKT | 1817 | X | XX | 25 | X | X |
|---|---|---|---|---|---|---|

TYPE

| Un = 06 = 63 V |
|---|
| Un = 01 = 100 V |
| Un = 25 = 250 V |
| Un = 40 = 400 V |

| TOLERANCE | |
|---|---|
| 4 | ± 5 % |
| 5 | ± 10 % |
| 6 | ± 20 % |

| PACKAGING | |
|---|---|
| G | Ammo, H = 18.5 mm |
| W | Reel H = 18.5 mm, diameter 350 mm |
| - | Bulk |

## SPECIFIC REFERENCE DATA

| DESCRIPTION | VALUE | | |
|---|---|---|---|
| Tangent of loss angle: | at 1 kHz | at 10 kHz | at 100 kHz |
| C ≤ 0.1 µF | ≤ 80 x $10^{-4}$ | ≤ 150 x $10^{-4}$ | ≤ 250 x $10^{-4}$ |
| 0.1 µF < C ≤ 1.0 µF | ≤ 80 x $10^{-4}$ | ≤ 150 x $10^{-4}$ | - |

| PITCH (mm) | RATED VOLTAGE PULSE SLOPE $(dU/dt)_R$ AT | | | |
|---|---|---|---|---|
| | 63 $V_{DC}$ | 100 $V_{DC}$ | 250 $V_{DC}$ | 400 $V_{DC}$ |
| 5 | 60 | 110 | 330 | 630 |

| | |
|---|---|
| If the maximum pulse voltage is less than the rated voltage higher dV/dt values can be permitted. | |
| R between leads, for C ≤ 0.33 µF and $U_R$ ≤ 100 V | > 15 000 MΩ |
| R between leads, for C ≤ 0.33 µF and $U_R$ > 100 V | > 30 000 MΩ |
| RC between leads, for C > 0.33 µF and $U_R$ ≤ 100 V | > 5000 s |
| RC between leads, for C > 0.33 µF and $U_R$ > 100 V | > 10 000 s |
| R between interconnecting leads and casing 100 V (foil method) | > 30 000 MΩ |
| Withstanding (DC) voltage (cut off current 10 mA) (1); rise time ≤ 1000 V/s | 1.6 x $U_{RDC}$, 1 min |
| Withstanding (DC) voltage between leads and case | 2.0 x $U_{RDC}$, with minimum of 200 $V_{DC}$; 1 min |
| Maximum application temperature | 100 °C for rated voltage 63 V<br>105 °C for rated voltage > 63 V |

**Note**

(1) See "Voltage Proof Test for Metalized Film Capacitors": www.vishay.com/doc?28169


For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## ELECTRICAL DATA

| $U_{RDC}$ (V) | CAP. (µF) | CAPACITANCE CODE | VOLTAGE CODE | $V_{AC}$ | DIMENSIONS w x h x l (mm) |
|---|---|---|---|---|---|
| 63 | 0.10 | -410 | 06 | 40 | 2.5 x 6.5 x 7.2 |
| | 0.15 | -415 | | | 2.5 x 6.5 x 7.2 |
| | 0.22 | -422 | | | 3.5 x 8.0 x 7.2 |
| | 0.33 | -433 | | | 3.5 x 8.0 x 7.2 |
| | 0.47 | -447 | | | 3.5 x 8.0 x 7.2 |
| | 0.68 | -468 | | | 4.5 x 9.0 x 7.2 |
| | 1.0 | -510 | | | 6.0 x 11.0 x 7.2 |
| 100 | 0.022 | -322 | 01 | 63 | 2.5 x 6.5 x 7.2 |
| | 0.033 | -333 | | | 2.5 x 6.5 x 7.2 |
| | 0.047 | -347 | | | 2.5 x 6.5 x 7.2 |
| | 0.068 | -368 | | | 2.5 x 6.5 x 7.2 |
| | 0.10 | -410 | | | 2.5 x 6.5 x 7.2 |
| | 0.15 | -415 | | | 3.5 x 8.0 x 7.2 |
| | 0.22 | -422 | | | 4.5 x 9.0 x 7.2 |
| | 0.33 | -433 | | | 4.5 x 9.0 x 7.2 |
| 250 | 0.0033 | -233 | 25 | 160 | 2.5 x 6.5 x 7.2 |
| | 0.0047 | -247 | | | 2.5 x 6.5 x 7.2 |
| | 0.0068 | -268 | | | 2.5 x 6.5 x 7.2 |
| | 0.010 | -310 | | | 2.5 x 6.5 x 7.2 |
| | 0.015 | -315 | | | 2.5 x 6.5 x 7.2 |
| | 0.022 | -322 | | | 3.5 x 8.0 x 7.2 |
| | 0.033 | -333 | | | 3.5 x 8.0 x 7.2 |
| | 0.047 | -347 | | | 4.5 x 9.0 x 7.2 |
| | 0.068 | -368 | | | 6.0 x 11.0 x 7.2 |
| | 0.10 | -410 | | | 6.0 x 11.0 x 7.2 |
| 250 | 0.0033 | -233 | 25 | 160 | 2.5 x 6.5 x 7.2 |
| | 0.0047 | -247 | | | 2.5 x 6.5 x 7.2 |
| | 0.0068 | -268 | | | 2.5 x 6.5 x 7.2 |
| | 0.010 | -310 | | | 2.5 x 6.5 x 7.2 |
| | 0.015 | -315 | | | 2.5 x 6.5 x 7.2 |
| | 0.022 | -322 | | | 3.5 x 8.0 x 7.2 |
| | 0.033 | -333 | | | 3.5 x 8.0 x 7.2 |
| | 0.047 | -347 | | | 4.5 x 9.0 x 7.2 |
| | 0.068 | -368 | | | 6.0 x 11.0 x 7.2 |
| | 0.10 | -410 | | | 6.0 x 11.0 x 7.2 |
| 400 | 0.0010 | -210 | 40 | 200 | 2.5 x 6.5 x 7.2 |
| | 0.0015 | -215 | | | 2.5 x 6.5 x 7.2 |
| | 0.0022 | -222 | | | 2.5 x 6.5 x 7.2 |
| | 0.0033 | -233 | | | 2.5 x 6.5 x 7.2 |
| | 0.0047 | -247 | | | 2.5 x 6.5 x 7.2 |
| | 0.0068 | -268 | | | 2.5 x 6.5 x 7.2 |
| | 0.010 | -310 | | | 3.5 x 8.0 x 7.2 |
| | 0.015 | -315 | | | 3.5 x 8.0 x 7.2 |
| | 0.022 | -322 | | | 4.5 x 9.0 x 7.2 |

## RECOMMENDED PACKAGING

| PACKAGING CODE | TYPE OF PACKAGING | HEIGHT (H) (mm) | REEL DIAMETER (mm) | ORDERING CODE EXAMPLES | PITCH 5 |
|---|---|---|---|---|---|
| G | Ammo | 18.5 | S [1] | MKT1817233255G | x |
| W | Reel | 18.5 | 350 | MKT1817233255W | x |
| - | Bulk | - | - | MKT1817233255 | x |

**Note**

[1] S = box size 55 mm x 210 mm x 340 mm (w x h x l)



For technical questions, contact: dc-film@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## MOUNTING

### Normal Use

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to packaging information www.vishay.com/docs?28139

### Specific Method of Mounting to Withstand Vibration and Shock

In order to withstand vibration and shock tests, it must be ensured that the stand-off pips are in good contact with the printed-circuit board.

- For pitches ≤ 15 mm the capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

### Space Requirements on Printed-Circuit Board

The maximum space for length ($l_{max.}$), width ($w_{max.}$) and height ($h_{max.}$) of film capacitors to take in account on the printed-circuit board is shown in the drawings.

- For products with pitch ≤ 15 mm, $\Delta w = \Delta l = 0.3$ mm; $\Delta h = 0.1$ mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.




## SOLDERING CONDITIONS

For general soldering conditions and wave soldering profile, we refer to the document “Characteristics and Definitions Used for Film Capacitors”: www.vishay.com/doc?28147

### Storage Temperature

$T_{stg}$ = -25 °C to +35 °C with RH maximum 75 % without condensation

### Ratings and Characteristics Reference Conditions

Unless otherwise specified, all electrical values apply to an ambient free air temperature of 23 °C ± 1 °C, an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of 50 % ± 2 %.

For reference testing, a conditioning period shall be applied over 96 h ± 4 h by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.


For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## CHARACTERISTICS




Capacitance as a function of ambient temperature (typical) for voltage 63 V




Capacitance as a function of ambient temperature (typical) for voltages > 63 V




Capacitance as a function of frequency (typical curve)




Impedance as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency


For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency




Max. AC voltage as a function of frequency


For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

**Maximum RMS Current (Sinewave) as a Function of Frequency**

The maximum RMS current is defined by $I_{ac} = \omega \times C \times U_{ac}$.

$U_{AC}$ is the maximum AC voltage depending on the ambient temperature in the curves "Max. RMS voltage and AC current as a function of frequency".




Tangent of loss angle as a function of frequency (typical curve)




Insulation resistance as a function of the ambient temperature (typical curve)




Max. DC and AC voltage as a function of temperature for voltage 63 V




Max. DC and AC voltage as a function of temperature for voltages > 63 V




Maximum allowed component temperature rise (ΔT) as a function of the ambient temperature $T_{amb}$ for voltage 63 V




Maximum allowed component temperature rise (ΔT) as a function of the ambient temperature $T_{amb}$ for voltages > 63 V



For technical questions, contact: dc-film@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| HEAT CONDUCTIVITY (G) AS A FUNCTION OF (ORIGINAL) PITCH AND CAPACITOR BODY THICKNESS IN mW/°C | |
|---|---|
| $W_{max.}$ (mm) | HEAT CONDUCTIVITY (mW/°C) |
| | PITCH 5 mm |
| 2.5 | 2.5 |
| 3.0 | 3.0 |
| 4.5 | 4.0 |
| 6.0 | 5.5 |

## POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free ambient temperature.
The power dissipation can be calculated according type detail specification “HQN-384-01/101: Technical Information Film Capacitors”.
The component temperature rise ($\Delta T$) can be measured (see section “Measuring the Component Temperature” for more details) or calculated by $\Delta T = P/G$:

- $\Delta T$ = component temperature rise (°C)
- P = power dissipation of the component (mW)
- G = heat conductivity of the component (mW/°C)

## MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:




The temperature is measured in unloaded ($T_{amb}$) and maximum loaded condition ($T_C$).
The temperature rise is given by $\Delta T = T_C - T_{amb}$.
To avoid radiation or convection, the capacitor should be tested in a wind-free box.


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## APPLICATION NOTE AND LIMITING CONDITIONS

These capacitors are not suitable for mains applications as across-the-line capacitors without additional protection, as described hereunder. These mains applications are strictly regulated in safety standards and therefore electromagnetic interference suppression capacitors conforming the standards must be used.

For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact: dc-film@vishay.com

To select the capacitor for a certain application, the following conditions must be checked:

1. The peak voltage ($U_P$) shall not be greater than the rated DC voltage ($U_{RDC}$)
2. The peak-to-peak voltage ($U_{P-P}$) shall not be greater than $2\sqrt{2} \times U_{RAC}$ to avoid the ionization inception level
3. The voltage peak slope (dU/dt) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by $U_{RDC}$ and divided by the applied voltage.
   For all other pulses following equation must be fulfilled:
   $$2 \times \int_0^T \left(\frac{dU}{dt}\right)^2 \times dt < U_{RDC} \times \left(\frac{dU}{dt}\right)_{rated}$$
   T is the pulse duration.
4. The maximum component surface temperature rise must be lower than the limits (see graph “Max. allowed component temperature rise”).
5. Since in circuits used at voltages over 280 V peak-to-peak the risk for an intrinsically active flammability after a capacitor breakdown (short circuit) increases, it is recommended that the power to the component is limited to 100 times the values mentioned in the table: “Heat Conductivity”
6. When using these capacitors as across-the-line capacitor in the input filter for mains applications or as series connected with an impedance to the mains the applicant must guarantee that the following conditions are fulfilled in any case (spikes and surge voltages from the mains included).

| VOLTAGE CONDITIONS FOR 6 ABOVE | | |
|---|---|---|
| **ALLOWED VOLTAGES** | **$T_{amb} \leq 85$ °C** | **85 °C < $T_{amb} \leq 100$ °C FOR 63 V** |
| | | **85 °C < $T_{amb} \leq 100$ °C FOR > 63 V** |
| Maximum continuous RMS voltage | $U_{RAC}$ | See “Max. AC voltage as function of temperature” per characteristics |
| Maximum temperature RMS-overvoltage (< 24 h) | 1.25 x $U_{RAC}$ | $U_{RAC}$ |
| Maximum peak voltage ($V_{O-P}$) (< 2 s) | 1.6 x $U_{RDC}$ | 1.3 x $U_{RDC}$ |

**Example**

C = 330 nF - 63 V used for the voltage signal shown in next drawing.
$U_{P-P}$ = 40 V; $U_P$ = 35 V; $T_1$ = 100 µs; $T_2$ = 200 µs
The ambient temperature is 35 °C

Checking conditions:

1. The peak voltage $U_P$ = 35 V is lower than 63 $V_{DC}$
2. The peak-to-peak voltage 40 V is lower than $2\sqrt{2} \times 40\ V_{AC}$ = 113 $U_{P-P}$
3. The voltage pulse slope (dU/dt) = 40 V/100 µs = 0.4 V/µs
   This is lower than 60 V/µs (see specific reference data for each version)
4. The dissipated power is 16.2 mW as calculated with fourier terms
   The temperature rise for $w_{max.}$ = 3.5 mm and pitch = 5 mm will be 16.2 mW/3.0 mW/°C = 5.4 °C
   This is lower than 15 °C temperature rise at 35 °C, according figure “Max. allowed component temperature rise”
5. Not applicable
6. Not applicable

**Voltage Signal**





For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## INSPECTION REQUIREMENTS

### General Notes

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-2 and Specific Reference Data”.

| GROUP C INSPECTION REQUIREMENTS | | |
|---|---|---|
| **SUB-CLAUSE NUMBER AND TEST** | **CONDITIONS** | **PERFORMANCE REQUIREMENTS** |
| **SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1** | | |
| 4.1 Dimensions (detail) | | As specified in chapters “MKT370 General Data” of this specification |
| 4.3.1 Initial measurements | Capacitance<br>Tangent of loss angle:<br>for C ≤ 470 nF at 100 kHz<br>for C > 470 nF at 10 kHz | |
| 4.3 Robustness of terminations | Tensile and bending | No visible damage |
| 4.4 Resistance to soldering heat | Method: 1A<br>Solder bath: 280 °C ± 5 °C<br>Duration: 10 s | |
| 4.14 Component solvent resistance | Isopropylalcohol at room temperature<br>Method: 2<br>Immersion time: 5 min ± 0.5 min<br>Recovery time: min. 1 h, max. 2 h | |
| 4.4.2 Final measurements | Visual examination | No visible damage<br>Legible marking |
| | Capacitance | $\lvert\Delta C/C\rvert \leq 2$ % of the value measured initially |
| | Tangent of loss angle | Increase of tan $\delta$:<br>≤ 0.005 for: C ≤ 100 nF or<br>≤ 0.010 for: 100 nF < C ≤ 220 nF or<br>≤ 0.015 for: 220 nF < C ≤ 470 nF or<br>≤ 0.003 for: C > 470 nF<br>Compared to values measured in 4.3.1 |
| **SUB-GROUP C1B OTHER PART OF SAMPLE OF SUB-GROUP C1** | | |
| 4.6.1 Initial measurements | Capacitance<br>Tangent of loss angle:<br>for C ≤ 470 nF at 100 kHz<br>for C > 470 nF at 10 kHz | |
| 4.6 Rapid change of temperature | θA = -55 °C<br>θB = +100 °C<br>5 cycles<br>Duration t = 30 min | |
| 4.7 Vibration | Visual examination<br>Mounting:<br>see section “Mounting” of this specification<br>Procedure B4<br>Frequency range: 10 Hz to 55 Hz<br>Amplitude: 0.75 mm or<br>Acceleration 98 m/s²<br>(whichever is less severe)<br>Total duration 6 h | No visible damage |


For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| GROUP C INSPECTION REQUIREMENTS | | |
|---|---|---|
| **SUB-CLAUSE NUMBER AND TEST** | **CONDITIONS** | **PERFORMANCE REQUIREMENTS** |
| **SUB-GROUP C1B OTHER PART OF SAMPLE OF SUB-GROUP C1** | | |
| 4.7.2 Final inspection | Visual examination | No visible damage |
| 4.9 Shock | Mounting:<br>see section “Mounting” of this specification<br>Pulse shape: half sine<br>Acceleration: 490 m/s²<br>Duration of pulse: 11 ms | |
| 4.9.3 Final measurements | Visual examination | No visible damage |
| | Capacitance | $\lvert\Delta C/C\rvert \leq 3$ % of the value measured in 4.6.1 |
| | Tangent of loss angle | Increase of tan δ:<br>≤ 0.010 for: C ≤ 220 nF or<br>≤ 0.015 for: 220 nF < C ≤ 470 nF or<br>≤ 0.003 for: C > 470 nF<br>Compared to values measured in 4.6.1 |
| | Insulation resistance | As specified in section “Specific Reference Data 370” of this specification |
| **SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B** | | |
| 4.10 Climatic sequence | | |
| 4.10.2 Dry heat | Temperature:<br>+100 °C for rated voltage 63 V<br>+105 °C for rated voltage > 63 V<br>Duration: 16 h | |
| 4.10.3 Damp heat cyclic<br>Test Db, first cycle | | |
| 4.10.4 Cold | Temperature: -55 °C<br>Duration: 2 h | |
| 4.10.6 Damp heat cyclic<br>Test Db, remaining cycles | Voltage proof = $U_{RDC}$ for 1 min within 15 min after removal from testchamber | No breakdown or flash-over |
| 4.10.6.2 Final measurements | Visual examination | No visible damage<br>Legible marking |
| | Capacitance | $\lvert\Delta C/C\rvert \leq 3$ % of the value measured in 4.4.2 or 4.9.3 |
| | Tangent of loss angle | Increase of tan δ:<br>≤ 0.010 for: C ≤ 220 nF or<br>≤ 0.015 for: 220 nF < C ≤ 470 nF or<br>≤ 0.005 for: C > 470 nF<br>Compared to values measured in 4.3.1 or 4.6.1 |
| | Insulation resistance | ≥ 50 % of values specified in section “Specific Reference Data 370” of this specification |


For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| GROUP C INSPECTION REQUIREMENTS | | |
|---|---|---|
| **SUB-CLAUSE NUMBER AND TEST** | **CONDITIONS** | **PERFORMANCE REQUIREMENTS** |
| **SUB-GROUP C2** | | |
| 4.11 Damp heat steady state | 56 days, 40 °C, 90 % to 95 % RH | |
| 4.11.1 Initial measurements | Capacitance<br>Tangent of loss angle at 1 kHz | |
| 4.11.3 Final measurements | Voltage proof = $U_{RDC}$ for 1 min within 15 min after removal from testchamber | No breakdown or flash-over |
| | Visual examination | No visible damage<br>Legible marking |
| | Capacitance | $\lvert\Delta C/C\rvert \leq 5$ % of the value measured in 4.11.1. |
| | Tangent of loss angle | Increase of tan $\delta$: $\leq 0.005$<br>Compared to values measured in 4.11.1 |
| | Insulation resistance | $\geq 50$ % of values specified in section "Specific Reference Data 370" of this specification |
| **SUB GROUP C3** | | |
| 4.12 Endurance | Duration: 2000 h<br>1.25 x $U_{RDC}$ at 85 °C<br>0.8 x 1.25 $U_{RDC}$ at 100 °C<br>for rated voltage 63 V<br>0.8 x 1.25 $U_{RDC}$ at 105 °C<br>for rated voltage > 63 V | |
| 4.12.1 Initial measurements | Capacitance<br>Tangent of loss angle:<br>for C ≤ 470 nF at 100 kHz<br>for C > 470 nF at 10 kHz | |
| 4.12.5 Final measurements | Visual examination | No visible damage<br>Legible marking |
| | Capacitance | $\lvert\Delta C/C\rvert \leq 5$ % compared to values measured in 4.12.1 |
| | Tangent of loss angle | Increase of tan $\delta$:<br>$\leq 0.005$ at 85 °C<br>$\leq 0.010$ at 100 °C for: C ≤ 220 nF or<br>$\leq 0.015$ for: 220 nF < C ≤ 470 nF or<br>$\leq 0.003$ for: C > 470 nF<br>Compared to values measured in 4.12.1 |
| | Insulation resistance | $\geq 50$ % of values specified in section "Specific Reference Data 370" of this specification |


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| GROUP C INSPECTION REQUIREMENTS | | |
|---|---|---|
| **SUB-CLAUSE NUMBER AND TEST** | **CONDITIONS** | **PERFORMANCE REQUIREMENTS** |
| **SUB-GROUP C4** | | |
| 4.13 Charge and discharge | 10 000 cycles<br>Charged to $U_{RDC}$<br><br>Discharge resistance:<br>$R = \frac{U_R}{C \times 2.5 \times (dU/dt)_R}$ | |
| 4.13.1 Initial measurements | Capacitance<br>Tangent of loss angle:<br>for C ≤ 470 nF at 100 kHz<br>for C > 470 nF at 10 kHz | |
| 4.13.3 Final measurements | Capacitance | \|ΔC/C\| ≤ 3 % compared to values measured in 4.13.1 |
| | Tangent of loss angle | Increase of tan δ:<br>≤ 0.005 for: C ≤ 100 nF or<br>≤ 0.010 for: 100 nF < C ≤ 220 nF or<br>≤ 0.015 for: 220 nF < C ≤ 470 nF or<br>≤ 0.003 for: C > 470 nF<br>Compared to values measured in 4.13.1 |
| | Insulation resistance | ≥ 50 % of values specified in section "Specific Reference Data 370" of this specification |


For technical questions, contact: dc-film@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

***© 2024 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED***