


Power Metal Strip® Resistors (Extended Range), Surface Mount



FEATURES

- 0805 size resistors with 0.25 W power rating
- Smaller footprint than a 1206 resistor (uses 40 % less board space)
- Superior overload and pulse handling capability
- SMD alternative for low power leaded wirewound resistors
- Low TCR 15 ppm/K
- Low noise: < - 40 dB
- Voltage coefficient: < 0.00001 %/V (< 0.1 ppm/V)
- Very low inductance: < 0.08 µH
- Compliant to RoHS Directive 2002/95/EC



STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	SIZE	POWER RATING $P_{70\text{ }^\circ\text{C}}$ W	LIMITING ELEMENT VOLTAGE V	TEMPERATURE COEFFICIENT \pm ppm/K	TOLERANCE \pm %	RESISTANCE RANGE Ω	E-SERIES
WSE0805	0805	0.25	$(P \times R)^{1/2}$	15, 25	0.1, 0.25, 0.5, 1.0	10 to 10K	96

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	WSE0805
Dielectric withstanding voltage	V_{AC}	200
Insulation resistance	Ω	$> 10^9$
Operating temperature range	$^\circ\text{C}$	- 65 to + 150
Weight/1000 pieces	g	5.5

GLOBAL PART NUMBER INFORMATION



Global Part Numbering example: WSE08051K500FXEA

W S E 0 8 0 5 1 K 5 0 0 F X E A

GLOBAL MODEL	RESISTANCE VALUE	TOLERANCE CODE	TCR CODE	PACKAGING CODE	SPECIAL
WSE0805	R = Decimal K = Thousand 100R0 = 100 Ω 4K000 = 4 k Ω	B = \pm 0.1 % C = \pm 0.25 % D = \pm 0.5 % F = \pm 1.0 %	X = \pm 15 ppm/K E = \pm 25 ppm/K	EA = Lead (Pb)-free, tape/reel EK = Lead (Pb)-free, bulk TG = Tin/Lead, tape/reel (RT1) BA = Tin/Lead, bulk (B43)	(Dash number) (Up to 2 digits) from 1 to 99 as applicable

* Pb containing terminations are not RoHS compliant, exemptions may apply



** Please see document "Vishay Material Category Policy": www.vishay.com/doc?99902

DIMENSIONS

RECOMMENDED LAND PATTERN


MODEL	DIMENSIONS in inches (millimeters)						
	D	L	W	T	G ⁽¹⁾	X ⁽¹⁾	Z ⁽¹⁾
WSE0805	0.015 ± 0.005 (0.38 ± 0.13)	0.080 ± 0.005 (2.30 ± 0.13)	0.050 ± 0.005 (1.27 ± 0.13)	0.025 max. (0.64 max.)	0.028 ± 0.004 (0.70 ± 0.10)	0.050 ± 0.004 (1.27 ± 0.10)	0.122 ± 0.004 (3.103 ± 0.10)

Note

⁽¹⁾ Land pattern dimensions (G, X, Z) are per IPC-782A.



PERFORMANCE		
TEST	CONDITIONS OF TEST	TEST LIMITS
Thermal shock	- 65 °C to + 150 °C, 100 cycles, 15 min at each extreme	± 0.10 % ΔR
Short time overload	5 x rated power for 5 s	± 0.10 % ΔR
Low temperature operation	- 65 °C, 0.25 W for 45 min	± 0.05 % ΔR
High temperature exposure	100 h at + 150 °C	± 0.10 % ΔR
Moisture resistance	MIL-STD-202, method 106, 0 % power, 7b not required	± 0.10 % ΔR
Load life	1000 h at 70 °C, 1.5 h "ON", 0.5 h "OFF"	± 0.05 % ΔR
Resistance to bonding exposure	260 °C for 10 s	± 0.10 % ΔR

PACKAGING				
MODEL	REEL			
	TAPE WIDTH	DIAMETER	PIECES/REEL	CODE
WSE0805	8 mm/punched paper	178 mm/7"	5000	EA

Note

- Embossed Carrier Tape per EIA-481.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.