

Metal Film Resistors, Zero Ohm Jumper, Industrial



FEATURES

- Provides low resistance circuit interconnections
- Color band marking for ease of identification after mounting
- Flame retardant coating
- Compatible with automatic insertion equipment
- Tape and reel packaging
- Compliant to RoHS directive 2002/95/EC



RoHS*
COMPLIANT

STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	HISTORICAL MODEL	MAXIMUM RESISTANCE VALUE mΩ	MAXIMUM CURRENT A	
			AT + 25 °C	AT + 150 °C
FRJ50	FRJ-50	10	25	0

Note

- DSCC has created a drawing to support the need for an axial-leaded zero-ohm jumper product. Vishay Dale is listed as a resource on this drawing as follows:

DSCC DRAWING NUMBER	VISHAY DALE MODEL	MAXIMUM RESISTANCE mΩ	MAXIMUM CURRENT RATING A
A-A-55502	FRJ50	10	5

This drawing can be viewed at: www.dsccl.dla.mil/Programs/MilSpec/ListDwgs.asp?DocType=DSCCdwg

TECHNICAL SPECIFICATIONS


PARAMETER	UNIT	FRJ50
Insulation Resistance - Dry	MΩ	10 000
Insulation Resistance - Wet	MΩ	100
Category Temperature Range	°C	- 55/+ 155
Dielectric Strength	- Atmospheric V_{RMS}	500
	- Reduced V_{RMS}	325
Failure Rate	$10^{-9}/h$	< 10
Weight	g	0.1

MATERIAL SPECIFICATIONS

Insulation Flammability	Self extinguishing 10 s after flame is removed	Solder plated copper	Tin-plated copper or tin/lead plated copper
-------------------------	--	----------------------	---



GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: FRJ50R36 (preferred part numbering format)



* Pb containing terminations are not RoHS compliant, exemptions may apply

DIMENSIONS in inches (millimeters)

FRJ50

MARKING

PACKAGING

Taped Lead and Reel Package

(52.4 mm inside tape spacing per EIA-296-E)

Notes

- Quantity per reel: 5000 pieces in 5000-piece increments
- A minimum of 12.0" (305 mm) bare tape leader shall be provided at each end of the reel
- Paper separator protection between layers of components
- Reel arbor hole is 1.25" (31.75 mm)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.