


## Thin Film 0304 Size Resistor on Alumina



Product may not be to scale

The CC6 series single-value resistor chips offer a small size, low shunt capacitance and solder pad option.

The CC6s nichrome resistor material offers excellent stability.

The CC6s are manufactured using Vishay Electro-Films (EFI) sophisticated thin film equipment and manufacturing technology. The CC6s are 100 % electrically tested and visually inspected to MIL-STD-883.

### FEATURES

- Wire bondable
- Chip size: 0.030 x 0.045 inches
- Resistance range: 20 Ω to 59 kΩ
- Alumina substrate
- Low stray capacitance: < 0.2 pF
- Resistor material: Nichrome
- Resistor passivation coat optional
- Tolerances to 0.05 %
- Solder pad optional

### APPLICATIONS


Vishay EFI CC6 chip resistors provide excellent high-frequency response and are ideally suited for prototyping.

Typical application areas are:

- Amplifiers
- Oscillators
- Attenuators
- Couplers
- Filters


Recommended for hermetic applications where die is not exposed to moisture.

### TEMPERATURE COEFFICIENT OF RESISTANCE, VALUES AND TOLERANCES



### STANDARD ELECTRICAL SPECIFICATIONS

PARAMETER	
Noise, MIL-STD-202, Method 308	- 20 dB typ.
Moisture Resistance, MIL-STD-202 Method 106 - Hermetic Applications	± 0.2 % max. $\Delta R/R$
Stability, 1000 h, + 125 °C, 65 mW	± 0.1 % max. $\Delta R/R$
Operating Temperature Range	- 55 °C to + 125 °C
Thermal Shock, MIL-STD-202, Method 107, Test Condition F	± 0.25 % max. $\Delta R/R$
High Temperature Exposure, + 150 °C, 100 h	± 0.1 % max. $\Delta R/R$
Dielectric Voltage Breakdown	400 V
Insulation Resistance	10 <sup>12</sup> min.
Operating Voltage	100 V max.
DC Power Rating at + 125 °C (Derated to Zero at + 150 °C)	65 mW max.
5 x Rated Power Short-Time Overload, + 25 °C, 5 s	± 0.25 % max. $\Delta R/R$

**DIMENSIONS** in inches

**SCHEMATIC**


<b>MECHANICAL SPECIFICATIONS</b> in inches	
PARAMETER	
Chip Size	0.030 x 0.045 ± 0.003 (0.762 x 1.143 ± 0.076 mm)
Chip Thickness	0.010 ± 0.002 (0.25 ± 0.05 mm)
Chip Substrate Material	99.6 % alumina, 2 - 4 microinch finish
Resistor Material	Nichrome
Bonding Pad Size	0.010 x 0.024 (0.254 x 0.61 mm) minimum
Number of Pads	2
Pad Material	25 kÅ minimum gold standard
Backing	None

**Options:** Terminations: Aluminum, nickel solder (62/32)  
 Gold back for solder die attach  
 Contact Applications Engineer

<b>ORDERING INFORMATION</b>						
Example: 100 % visual, 50 Ω, ± 10 %, ± 50 ppm/°C TCR, gold terminations						
W	CC6	5000	B	K	D	G
INSPECTION/ PACKAGING	PRODUCT FAMILY	RESISTANCE VALUE	MULTIPLIER CODE	TOLERANCE CODE	TCR	TERMINATIONS
W = 100 % visually inspected parts in matrix tray per MIL-STD-883 X = Sample, commercial visually inspected parts loaded in matrix trays (4 % AQL)		Use first 4 or 5 significant digits of resistance	<b>B</b> = 0.01 <b>A</b> = 0.1 <b>0</b> = 1 <b>1</b> = 10 <b>2</b> = 100	<b>A</b> = 0.05 %* <b>B</b> = 0.1 %* <b>C</b> = 0.25 %* <b>D</b> = 0.5 % <b>F</b> = 1.0 % <b>G</b> = 2.0 % <b>J</b> = 5.0 % <b>K</b> = 10 % *Coating standard	<b>A</b> = ± 10 ppm/°C <b>B</b> = ± 25 ppm/°C <b>D</b> = ± 50 ppm/°C <b>E</b> = ± 100 ppm/°C	<b>G</b> = Gold <b>S</b> = Solder



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.