



Thin Film Resistors on Silicon, User Trimmable



Product may not be to scale

The SC7 and SCB series resistor chips offer a combination of nichrome user trimmability as a single resistor or as a ratio trim while maintaining the excellent TCR tracking characteristics of two resistors on the same chip. The SC7 and SCBs are manufactured using Vishay Electro-Films (EFI) sophisticated thin film equipment and manufacturing technology. The SC7 and SCBs are 100 % electrically tested and visually inspected to MIL-STD-883.

FEATURES

- Wire bondable
- Chip sizes
SC7 - 0.030 inches square
SCB - 0.050 inches square
- Resistance range R_T : 100 Ω to 20 k Ω for SC7
Resistance range R_T : 100 Ω to 50 k Ω for SCB
- Silicon substrate
- Power: 250 or 400 mW capability
- Resistor material: Nichrome
- User trimmable


APPLICATIONS

Vishay EFI SC7 and SCB chip resistors have excellent power dissipation capability and are ideally suited for prototyping. Typical application areas are:

- Amplifiers
- Oscillators
- Attenuators
- Couplers
- Filters

Recommended for hermetic environments where die is not exposed to moisture

TEMPERATURE COEFFICIENT OF RESISTANCE, VALUES AND TOLERANCES



PROCESS CODE			
SC7		SCB	
CLASS H*	CLASS K*	CLASS H*	CLASS K*
220	224	220	224
221	225	221	225
222	226	222	226



*MIL-PRF-38534 inspection criteria
 R_A user trimmable 50 % above
 R_T value specified in P/N

STANDARD ELECTRICAL SPECIFICATIONS

PARAMETER	
Noise, MIL-STD-202, Method 308	- 20 dB typ.
Stability, 1000 h, + 125 °C at Rated Power	± 0.2 % max. $\Delta R/R$
Operating Temperature Range	- 55 °C to + 125 °C
Thermal Shock, MIL-STD-202, Method 107, Test Condition F	± 0.25 % max. $\Delta R/R$
High Temperature Exposure, + 150 °C, 100 h	± 0.25 % max. $\Delta R/R$
Dielectric Voltage Breakdown	200 V
Insulation Resistance	10^{12} min.
Operating Voltage	100 V max.
DC Power Rating at 70 °C Derated to Zero at 150 °C	250 mW max. (0.030 inches) 400 mW max. (0.050 inches)
5 x Rated Power Short-Time Overload, + 25 °C, 5 s	+ 0.25 % max. $\Delta R/R$

Note:

- Performance characteristics are not guaranteed once user trimmed

DIMENSIONS in inches

SCHEMATIC


MECHANICAL SPECIFICATIONS in inches	
PARAMETER	
Chip Size	0.030 x 0.030 ± 0.003 (0.76 x 0.76 ± 0.076 mm) 0.050 x 0.050 ± 0.003 (1.27 x 1.27 ± 0.076 mm)
Chip Thickness	0.010 ± 0.002 (0.25 ± 0.05 mm)
Chip Substrate Material	Oxidized silicon, 10 kÅ minimum SiO ₂
Resistor Material	Nichrome
Bonding Pad Size	0.005 x 0.005 (0.127 x 0.127 mm) minimum
Number of Pads	6
Pad Material	15 kÅ minimum gold standard
Backing	None, lapped semiconductor silicon

Options: Gold back for solder die attach
Consult Application Engineer

ORDERING INFORMATION					
Example: 100 % visualled, $R_T = 500$, ± 10 %, ± 50 ppm/°C TCR, R_A user trim gold pads, class H visual inspection Standard user trim versions will be supplied with R_A untrimmed For custom R_A , R_B combinations consult Application Engineer					
W	SC7	221	5000	A	K
INSPECTION/ PACKAGING	PRODUCT FAMILY	PROCESS CODE	RESISTANCE VALUE	MULTIPLIER CODE	TOLERANCE CODE
W = 100 % visually inspected parts in matrix MIL-STD-883 X = Sample, commercial visually inspected parts loaded in matrix trays (4 % AQL)	SC7 SCB	See Process Code table	Use first 4 digits significant digits of the resistance (R_T)	B = 0.01 A = 0.1 0 = 1 1 = 10	B = 0.1 % D = 0.5 % F = 1.0 % G = 2.0 % H = 2.5 % J = 5.0 % K = 10 % M = 20 %



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.