




R-C Thermal Model Parameters

DESCRIPTION

The parametric values in the R-C thermal model have been derived using curve-fitting techniques. R-C values for the electrical circuit in the Foster/tank and Cauer/filter configurations are included. When implemented in PSpice, these values have matching characteristic curves to the single-pulse transient thermal impedance curves for the MOSFET.

These RC values can be used in the PSpice simulation to evaluate the thermal behavior of the MOSFET junction temperature under a defined power profile. These techniques are described in application note AN609, "Thermal Simulation of Power MOSFETs on the PSpice Platform".

R-C THERMAL MODEL FOR TANK CONFIGURATION



R-C VALUES FOR TANK CONFIGURATION			
THERMAL RESISTANCE (°C/W)			
Junction to	Ambient	Case	Foot
RT1	7.9892	235.0966m	n/a
RT2	6.1462	210.2906m	n/a
RT3	1.3297	197.5175m	n/a
RT4	34.2342	463.3200m	n/a
THERMAL CAPACITANCE (Joules/°C)			
Junction to	Ambient	Case	Foot
CT1	502.0322m	311.6261m	n/a
CT2	37.9055m	271.7331m	n/a
CT3	1.8534m	3.4471m	n/a
CT4	1.1773	79.8622m	n/a


Note

- n/a indicates not applicable

This document is intended as a SPICE modeling guideline and does not constitute a commercial product datasheet. Designers should refer to the appropriate datasheet of the same number for guaranteed specification limits.



R-C THERMAL MODEL FOR FILTER CONFIGURATION



255.8682m

R-C VALUES FOR FILTER CONFIGURATION			
THERMAL RESISTANCE (°C/W)			
Junction to	Ambient	Case	Foot
RF1	1.9114	228.9653m	n/a
RF2	7.3614	855.9588m	n/a
RF3	14.6731	6.6404m	n/a
RF4	25.7778	5.0360m	n/a
THERMAL CAPACITANCE (Joules/°C)			
Junction to	Ambient	Case	Foot
CF1	3.1551m	3.3886m	n/a
CF2	37.2700m	49.9141m	n/a
CF3	373.1761m	18.4650	n/a
CF4	1.0452	1.2887m	n/a

Note

- n/a indicates not applicable

