



## Bidirectional Symmetrical (BiSy) Low Capacitance, Single-Line ESD-Protection Diode in LLP1006-2M


**FEATURES**

- Ultra compact LLP1006-2M package
- Low package height < 0.4 mm
- 1-line ESD-protection
- Working range  $\pm 5.5$  V
- Low leakage current  $I_R < 0.1 \mu\text{A}$
- Very low load capacitance  $C_D = 0.3$  pF
- ESD-protection acc. IEC 61000-4-2  
 $\pm 15$  kV contact discharge  
 $\pm 16$  kV air discharge
- Soldering can be checked by standard vision inspection; no X-ray necessary
- Pin plating NiPdAu (e4) no whisker growth
- e4 - precious metal (e.g. Ag, Au, NiPd, NiPdAu) (no Sn)
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC


**MARKING** (example only)


Bar = pin 1 marking

X = date code

Y = type code (see table below)

| ORDERING INFORMATION |                   |  |                        |
|----------------------|-------------------|--|------------------------|
| DEVICE NAME          | ORDERING CODE     | TAPED UNITS PER REEL<br>(8 mm TAPE ON 7" REEL) | MINIMUM ORDER QUANTITY |
| VBUS05L1-DD1         | VBUS05L1-DD1-G-08 | 8000   | 8000                   |

| PACKAGE DATA |              |           |         |   |                                      |                          |
|--------------|--------------|-----------|---------|---|--------------------------------------|--------------------------|
| DEVICE NAME  | PACKAGE NAME | TYPE CODE | WEIGHT  | MOLDING COMPOUND<br>FLAMMABILITY RATING | MOISTURE SENSITIVITY LEVEL           | SOLDERING CONDITIONS     |
| VBUS05L1-DD1 | LLP1006-2M   | R         | 0.72 mg | UL 94 V-0                               | MSL level 1<br>(according J-STD-020) | 260 °C/10 s at terminals |

| ABSOLUTE MAXIMUM RATINGS VBUS05L1-DD1 |  |           |               |      |
|---------------------------------------|--|-----------|---------------|------|
| PARAMETER                             | TEST CONDITIONS  | SYMBOL    | VALUE         | UNIT |
| Peak pulse current                    | Acc. IEC 61000-4-5; $t_p = 8/20 \mu\text{s}$ ; single shot                 | $I_{PPM}$ | 2             | A    |
| Peak pulse power                      | Pin 1 to pin 2, acc. IEC 61000-4-5; $t_p = 8/20 \mu\text{s}$ ; single shot | $P_{PP}$  | 34            | W    |
| ESD immunity                          | Contact discharge acc. IEC 61000-4-2; 10 pulses                            | $V_{ESD}$ | $\pm 15$      | kV   |
|                                       | Air discharge acc. IEC 61000-4-2; 10 pulses                                |           | $\pm 16$      | kV   |
| Operating temperature                 | Junction temperature   | $T_J$     | - 40 to + 125 | °C   |
| Storage temperature                   |  | $T_{STG}$ | - 40 to + 150 | °C   |

| ELECTRICAL CHARACTERISTICS VBUS05L1-DD1 ( $T_{amb} = 25 \text{ }^\circ\text{C}$ , unless otherwise specified) |  |               |      |      |      |               |
|---|--|---------------|------|------|------|---------------|
| PARAMETER   | TEST CONDITIONS/REMARKS                | SYMBOL        | MIN. | TYP. | MAX. | UNIT          |
| Protection paths  | Number of lines which can be protected | $N_{channel}$ | -    | -    | 1    | lines         |
| Reverse stand-off voltage   | at $I_R = 0.05 \mu\text{A}$            | $V_{RWM}$     | 5.5  | -    | -    | V             |
| Reverse current   | at $V_R = 5.5$ V                       | $I_R$         | -    | -    | 0.05 | $\mu\text{A}$ |
| Reverse breakdown voltage   | at $I_R = 1$ mA                        | $V_{BR}$      | 7    | 8.4  | 9.5  | V             |
| Reverse clamping voltage  | at $I_{PP} = 1$ A                      | $V_C$         | -    | 11.5 | 14   | V             |
|   | at $I_{PP} = I_{PPM} = 2$ A            | $V_C$         | -    | 14   | 17   | V             |
| Capacitance   | at $V_R = 0$ V, $f = 1$ MHz            | $C_D$         | -    | 0.33 | 0.4  | pF            |
|   | at $V_R = 2.5$ V, $f = 1$ MHz          | $C_D$         | -    | 0.34 | -    | pF            |

 \*\* Please see document "Vishay Material Category Policy": [www.vishay.com/doc?99902](http://www.vishay.com/doc?99902)

## VBUS05L1-DD1: ESD PROTECTION WITH LOWEST LOAD CAPACITANCE

The **VBUS05L1-DD1** is a Bidirectional and Symmetrical (BiSy) ESD-protection device which clamps positive and negative overvoltage transients to ground. Connected between the signal or data line and the ground the **VBUS05L1-DD1** offers a high isolation (low leakage current, lowest capacitance) within the specified working range. Due to the short leads and small package size of the tiny LLP1006-2M package the line inductance is very low, so that fast transients like an ESD-strike can be clamped with minimal over- or undershoots.

### TYPICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - ESD Discharge Current Wave Form acc. IEC 61000-4-2 (330  $\Omega$ /150 pF)




Fig. 3 - Typical Capacitance  $C_D$  vs. Reverse Voltage  $V_R$




Fig. 2 - 8/20  $\mu\text{s}$  Peak Pulse Current Wave Form acc. IEC 61000-4-5




Fig. 4 - Typical Reverse Voltage  $V_R$  vs. Reverse Current  $I_R$

**Bidirectional Symmetrical (BiSy) Low  
 Capacitance, Single-Line ESD-Protection Diode  
 in LLP1006-2M**

Vishay Semiconductors




Fig. 5 - Typical Peak Clamping Voltage  $V_C$  vs. Peak Pulse Current  $I_{PP}$




Fig. 8 - Typical Peak Clamping Voltage at ESD Contact Discharge (acc. IEC 61000-4-2)




Fig. 6 - Typical Clamping Performance at + 8 kV Contact Discharge (acc. IEC 61000-4-2)




Fig. 7 - Typical Clamping Performance at - 8 kV Contact Discharge (acc. IEC 61000-4-2)


# VBUS05L1-DD1



Vishay Semiconductors

Bidirectional Symmetrical (BiSy) Low Capacitance, Single-Line ESD-Protection Diode in LLP1006-2M

**PACKAGE DIMENSIONS** in millimeters (inches): **LLP1006-2M**



Document no.:S8-V-3906.04-019 (4)

Created - Date: 24.June.2009

21798



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**