

Insulated Gate Bipolar Transistor Ultralow $V_{CE(on)}$, 250 A


SOT-227
FEATURES

- Standard: optimized for minimum saturation voltage and low speed
- Lowest conduction losses available
- Fully isolated package (2500 V_{AC})
- Very low internal inductance (5 nH typical)
- Industry standard outline
- Designed and qualified for industrial level
- UL approved file E78996
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


**RoHS
COMPLIANT**

| PRODUCT SUMMARY | |
|--|------------------------|
| V_{CES} | 600 V |
| $V_{CE(on)}$ (typical) at 200 A, 25 °C | 1.33 V |
| I_C at $T_C = 90$ °C ⁽¹⁾ | 250 A |
| Speed | DC to 1 kHz |
| Package | SOT-227 |
| Circuit | Single switch no diode |

Note

- ⁽¹⁾ Maximum collector current admitted 100 A to do not exceed the maximum temperature of terminals

BENEFITS

- Designed for increased operating efficiency in power conversion: UPS, SMPS, TIG welding, induction heating
- Easy to assemble and parallel
- Direct mounting to heatsink
- Plug-in compatible with other SOT-227 packages

| ABSOLUTE MAXIMUM RATINGS | | | | |
|--------------------------------|----------------------|---|----------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | MAX. | UNITS |
| Collector to emitter voltage | V_{CES} | | 600 | V |
| Continuous collector current | I_C ⁽¹⁾ | $T_C = 25$ °C | 400 | A |
| | | $T_C = 90$ °C | 250 | |
| Pulsed collector current | I_{CM} | Repetitive rating; $V_{GE} = 20$ V, pulse width limited by maximum junction temperature | 400 | |
| Clamped Inductive load current | I_{LM} | $V_{CC} = 80$ % (V_{CES}), $V_{GE} = 20$ V, $L = 10$ μ H, $R_g = 2.0$ Ω | 400 | |
| Gate to emitter voltage | V_{GE} | | ± 20 | V |
| Power dissipation | P_D | $T_C = 25$ °C | 961 | W |
| | | $T_C = 90$ °C | 462 | |
| Isolation voltage | V_{ISOL} | Any terminal to case, $t = 1$ min | 2500 | V |

Note

- ⁽¹⁾ Maximum collector current admitted 100 A to do not exceed the maximum temperature of terminals

| THERMAL AND MECHANICAL SPECIFICATIONS | | | | | | |
|--|----------------|-----------------------|------|------|------------|-------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | MIN. | TYP. | MAX. | UNITS |
| Junction and storage temperature range | T_J, T_{Stg} | | -40 | - | 150 | °C |
| Thermal resistance junction to case | R_{thJC} | | - | - | 0.13 | °C/W |
| Thermal resistance case to heatsink | R_{thCS} | Flat, greased surface | - | 0.05 | - | |
| Weight | | | - | 30 | - | g |
| Mounting torque | | Torque to terminal | - | - | 1.1 (9.7) | Nm (lbf.in) |
| | | Torque to heatsink | - | - | 1.3 (11.5) | Nm (lbf.in) |
| Case style | | SOT-227 | | | | |



| ELECTRICAL SPECIFICATIONS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | | | | | |
|---|--------------------------------|--|------|------|-----------|---------------|---|
| PARAMETER | SYMBOL | TEST CONDITIONS | MIN. | TYP. | MAX. | UNITS | |
| Collector to emitter breakdown voltage | $V_{(BR)CES}$ | $V_{GE} = 0\text{ V}, I_C = 1\text{ mA}$ | 600 | - | - | | |
| Emitter to collector breakdown voltage | $V_{(BR)ECS}^{(1)}$ | $V_{GE} = 0\text{ V}, I_C = 1.0\text{ A}$ | 18 | - | - | | |
| Collector to emitter voltage | $V_{CE(on)}$ | $I_C = 100\text{ A}$ | - | 1.10 | 1.3 | V | |
| | | $I_C = 200\text{ A}$ | | 1.33 | 1.66 | | |
| | | $I_C = 100\text{ A}, T_J = 125\text{ }^\circ\text{C}$ | | - | 1.02 | | - |
| | | $I_C = 200\text{ A}, T_J = 125\text{ }^\circ\text{C}$ | | - | 1.32 | | - |
| | | $I_C = 100\text{ A}, T_J = 150\text{ }^\circ\text{C}$ | | - | 1.02 | | - |
| | | $I_C = 200\text{ A}, T_J = 150\text{ }^\circ\text{C}$ | | - | 1.33 | | - |
| Gate threshold voltage | $V_{GE(th)}$ | $V_{CE} = V_{GE}, I_C = 250\text{ }\mu\text{A}$ | 3.0 | 4.5 | 6.0 | | |
| | | $V_{CE} = V_{GE}, I_C = 250\text{ }\mu\text{A}, T_J = 125\text{ }^\circ\text{C}$ | - | 3.1 | - | | |
| Temperature coefficient of threshold voltage | $\Delta V_{GE(th)}/\Delta T_J$ | $V_{CE} = V_{GE}, I_C = 1\text{ mA}, 25\text{ }^\circ\text{C to } 125\text{ }^\circ\text{C}$ | - | -12 | - | mV/°C | |
| Collector to emitter leakage current | I_{CES} | $V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}$ | - | 20 | 1000 | μA | |
| | | $V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}, T_J = 125\text{ }^\circ\text{C}$ | - | 0.2 | - | mA | |
| | | $V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}, T_J = 150\text{ }^\circ\text{C}$ | - | 0.6 | 10 | | |
| Gate to emitter leakage current | I_{GES} | $V_{GE} = \pm 20\text{ V}$ | - | - | ± 250 | nA | |

Notes

(1) Pulse width $\leq 80\text{ }\mu\text{s}$; duty factor $\leq 0.1\text{ }%$

| SWITCHING CHARACTERISTICS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified) | | | | | | | |
|---|--------------|---|---|--------|------|-------|----|
| PARAMETER | SYMBOL | TEST CONDITIONS | MIN. | TYP. | MAX. | UNITS | |
| Total gate charge (turn-on) | Q_g | $I_C = 100\text{ A}, V_{CC} = 600\text{ V}, V_{GE} = 15\text{ V}$ | - | 770 | 1200 | nC | |
| Gate-to-emitter charge (turn-on) | Q_{ge} | | - | 100 | 150 | | |
| Gate-to-collector charge (turn-on) | Q_{gc} | | - | 260 | 380 | | |
| Turn-on switching loss | E_{on} | $T_J = 25\text{ }^\circ\text{C}$ $I_C = 100\text{ A}$ $V_{CC} = 480\text{ V}$ $V_{GE} = 15\text{ V}$ $R_g = 5.0\text{ }\Omega$ $L = 500\text{ }\mu\text{H}$ | - | 0.55 | - | mJ | |
| Turn-off switching loss | E_{off} | | - | 25 | - | | |
| Total switching loss | E_{tot} | | - | 25.5 | - | | |
| Turn-on delay time | $t_{d(on)}$ | | Energy losses include tail and diode recovery. Diode used 60APH06 | - | 267 | - | ns |
| Rise time | t_r | | | - | 42 | - | |
| Turn-off delay time | $t_{d(off)}$ | | | - | 310 | - | |
| Fall time | t_f | - | | 450 | - | | |
| Turn-on switching loss | E_{on} | $T_J = 125\text{ }^\circ\text{C}$ $I_C = 100\text{ A}$ $V_{CC} = 480\text{ V}$ $V_{GE} = 15\text{ V}$ $R_g = 5.0\text{ }\Omega$ $L = 500\text{ }\mu\text{H}$ | - | 0.67 | - | mJ | |
| Turn-off switching loss | E_{off} | | - | 43.0 | - | | |
| Total switching loss | E_{tot} | | - | 43.7 | - | | |
| Turn-on delay time | $t_{d(on)}$ | | Energy losses include tail and diode recovery. Diode used 60APH06 | - | 275 | - | ns |
| Rise time | t_r | | | - | 50 | - | |
| Turn-off delay time | $t_{d(off)}$ | | | - | 350 | - | |
| Fall time | t_f | - | | 700 | - | | |
| Internal emitter inductance | L_E | Between lead and center of die contact | - | 5.0 | - | nH | |
| Input capacitance | C_{ies} | $V_{GE} = 0\text{ V}, V_{CC} = 30\text{ V}, f = 1.0\text{ MHz}$ | - | 16 250 | - | pF | |
| Output capacitance | C_{oes} | | - | 1040 | - | | |
| Reverse transfer capacitance | C_{res} | | - | 190 | - | | |




Fig. 1 - Maximum DC IGBT Collector Current vs. Case Temperature




Fig. 4 - Typical IGBT Zero Gate Voltage Collector Current




Fig. 2 - Typical Collector to Emitter Current Output Characteristics




Fig. 5 - Typical IGBT Threshold Voltage




Fig. 3 - Typical IGBT Transfer Characteristics




Fig. 6 - Typical IGBT Collector to Emitter Voltage vs. Junction Temperature, $V_{GE} = 15\text{ V}$




Fig. 7 - Typical IGBT Energy Losses vs. I_C , $T_J = 125\text{ }^\circ\text{C}$, $V_{CC} = 480\text{ V}$, $V_{GE} = 15\text{ V}$, $L = 500\text{ }\mu\text{H}$, $R_g = 5\text{ }\Omega$, Diode used: 60APH06




Fig. 9 - Typical IGBT Energy Losses vs. R_g , $T_J = 125\text{ }^\circ\text{C}$, $I_C = 200\text{ A}$, $V_{CC} = 480\text{ V}$, $V_{GE} = 15\text{ V}$, $L = 500\text{ }\mu\text{H}$, Diode used: 60APH06




Fig. 8 - Typical IGBT Switching Time vs. I_C , $T_J = 125\text{ }^\circ\text{C}$, $V_{CC} = 480\text{ V}$, $V_{GE} = 15\text{ V}$, $L = 500\text{ }\mu\text{H}$, $R_g = 5\text{ }\Omega$, Diode used: 60APH06




Fig. 10 - Typical IGBT Switching Time vs. R_g , $T_J = 125\text{ }^\circ\text{C}$, $I_C = 200\text{ A}$, $V_{CC} = 480\text{ V}$, $V_{GE} = 15\text{ V}$, $L = 500\text{ }\mu\text{H}$, Diode used: 60APH06




Fig. 11 - Maximum Thermal Impedance Z_{thJC} Characteristics




Fig. 12 - Typical Load Current vs. Frequency (Load Current = I_{RMS} of Fundamental)




Fig. 13 - Typical Capacitance vs. Collector to Emitter Voltage




Fig. 14 - Typical Gate Charge vs. Gate to Emitter Voltage





Fig. 15 - Turn-Off SOA



* Driver same type as D.U.T.; $V_C = 80\%$ of V_{CE} (max)

Note: Due to the 50 V power supply, pulse width and inductor will increase to obtain rated I_d

Fig. 16a - Clamped Inductive Load Test Circuit





Fig. 16b - Pulsed Collector Current Test Circuit



* Driver same type as D.U.T., $V_C = 480$ V

Fig. 17a - Switching Lost Test Circuit




Fig. 17b - Switching Loss Waveforms

ORDERING INFORMATION TABLE

| | | | | | | | | |
|-------------|------------|----------|----------|------------|----------|----------|-----------|----------|
| Device code | VS- | G | A | 250 | S | A | 60 | S |
| | ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ | ⑧ |

- 1** - Vishay Semiconductors product
- 2** - Insulated Gate Bipolar Transistor (IGBT)
- 3** - Gen 4, IGBT silicon
- 4** - Current rating (250 = 250 A)
- 5** - Circuit configuration (S = single switch, without antiparallel diode)
- 6** - Package indicator (A = SOT-227)
- 7** - Voltage rating (60 = 600 V)
- 8** - Speed/type (S = standard speed)


| CIRCUIT CONFIGURATION | | |
|--------------------------------------|----------------------------|-----------------|
| CIRCUIT | CIRCUIT CONFIGURATION CODE | CIRCUIT DRAWING |
| Single switch, no antiparallel diode | S | |

| LINKS TO RELATED DOCUMENTS | |
|----------------------------|--|
| Dimensions | www.vishay.com/doc?95423 |
| Packaging information | www.vishay.com/doc?95425 |



SOT-227 Generation II

DIMENSIONS in millimeters (inches)



Note

- Controlling dimension: millimeter



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.