

## Silicon Phototransistor in 0805 Package



20043-1

### DESCRIPTION

TEMT7100ITX01 is a silicon NPN epitaxial planar phototransistor with daylight blocking filter in a miniature, black 0805 package for surface mounting. Filter bandwidth is matched with 830 nm to 950 nm IR emitters.

### FEATURES

- Package type: surface mount
- Package form: 0805
- Dimensions (L x W x H in mm): 2 x 1.25 x 0.85
- AEC-Q101 qualified
- Enhanced operating temperature range: top = -40 °C to +110 °C
- High photo sensitivity
- Daylight blocking filter matches with 830 nm to 950 nm IR emitters
- Angle of half sensitivity:  $\phi = \pm 60^\circ$
- Package matched with IR emitter series VSMB1940X01
- Floor life: 72 h, MSL 4, acc. J-STD-020
- Lead (Pb)-free reflow soldering
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

AUTOMOTIVE  
GRADE

**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### APPLICATIONS

- Detector in automotive applications
- Photo interrupters
- Miniature switches
- Counters
- Encoders
- Position sensors

### PRODUCT SUMMARY

| COMPONENT     | $I_{caE}$ (μA) | $\phi$ (deg) | $\lambda_{0.5}$ (nm) |
|---------------|----------------|--------------|----------------------|
| TEMT7100ITX01 | 225 to 675     | $\pm 60$     | 750 to 1010          |

#### Note

- Test condition see table "Basic Characteristics"

### ORDERING INFORMATION

| ORDERING CODE | PACKAGING     | REMARKS                      | PACKAGE FORM |
|---------------|---------------|------------------------------|--------------|
| TEMT7100ITX01 | Tape and reel | MOQ: 3000 pcs, 3000 pcs/reel | 0805         |

#### Note

- MOQ: minimum order quantity

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25^\circ\text{C}$ , unless otherwise specified)

| PARAMETER                           | TEST CONDITION                  | SYMBOL     | VALUE       | UNIT             |
|-------------------------------------|---------------------------------|------------|-------------|------------------|
| Collector emitter voltage           |                                 | $V_{CEO}$  | 20          | V                |
| Emitter collector voltage           |                                 | $V_{ECO}$  | 7           | V                |
| Collector current                   |                                 | $I_C$      | 20          | mA               |
| Power power dissipation             | $T_{amb} \leq 55^\circ\text{C}$ | $P_V$      | 100         | mW               |
| Junction temperature                |                                 | $T_j$      | 110         | $^\circ\text{C}$ |
| Operating temperature range         |                                 | $T_{amb}$  | -40 to +110 | $^\circ\text{C}$ |
| Storage temperature range           |                                 | $T_{stg}$  | -40 to +110 | $^\circ\text{C}$ |
| Soldering temperature               | Acc. reflow profile fig. 8      | $T_{sd}$   | 260         | $^\circ\text{C}$ |
| Thermal resistance junction/ambient | Acc. J-STD-051                  | $R_{thJA}$ | 270         | K/W              |




Fig. 1 - Power Dissipation Limit vs. Ambient Temperature

| <b>BASIC CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                        |                 |      |             |      |               |
|-----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|-----------------|------|-------------|------|---------------|
| PARAMETER                                                                                           | TEST CONDITION                                                         | SYMBOL          | MIN. | TYP.        | MAX. | UNIT          |
| Collector emitter breakdown voltage                                                                 | $I_C = 0.1\text{ mA}$                                                  | $V_{CEO}$       | 20   |             |      | V             |
| Collector dark current                                                                              | $V_{CE} = 5\text{ V}, E = 0$                                           | $I_{CEO}$       |      | 1           | 100  | nA            |
| Collector emitter capacitance                                                                       | $V_{CE} = 0\text{ V}, f = 1\text{ MHz}, E = 0$                         | $C_{CEO}$       |      | 25          |      | pF            |
| Collector light current                                                                             | $E_e = 1\text{ mW/cm}^2, \lambda = 950\text{ nm}, V_{CE} = 5\text{ V}$ | $I_{CA}$        | 225  | 450         | 675  | $\mu\text{A}$ |
| Angle of half sensitivity                                                                           |                                                                        | $\phi$          |      | $\pm 60$    |      | deg           |
| Wavelength of peak sensitivity                                                                      |                                                                        | $\lambda_p$     |      | 870         |      | nm            |
| Range of spectral bandwidth                                                                         |                                                                        | $\lambda_{0.5}$ |      | 750 to 1010 |      | nm            |
| Collector emitter saturation voltage                                                                | $I_C = 0.05\text{ mA}$                                                 | $V_{CEsat}$     |      |             | 0.4  | V             |
| Temperature coefficient of $I_{ca}$                                                                 | $E_e = 1\text{ mW/cm}^2, \lambda = 950\text{ nm}, V_{CE} = 5\text{ V}$ | $Tk_{Ica}$      |      | 1.1         |      | %/K           |

### BASIC CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 2 - Collector Dark Current vs. Ambient Temperature




Fig. 3 - Collector Light Current vs. Irradiance




Fig. 4 - Rise/Fall Time vs. Collector Current




Fig. 6 - Relative Radiant Sensitivity vs. Angular Displacement




Fig. 5 - Relative Spectral Sensitivity vs. Wavelength




Fig. 7 - Relative Collector Current vs. Ambient Temperature

## REFLOW SOLDER PROFILE




Fig. 8 - Lead (Pb)-free Reflow Solder Profile acc. J-STD-020

## DRYPACK

Devices are packed in moisture barrier bags (MBB) to prevent the products from moisture absorption during transportation and storage. Each bag contains a desiccant.

## FLOOR LIFE

Floor life (time between soldering and removing from MBB) must not exceed the time indicated on MBB label:

Floor life: 72 h

Conditions:  $T_{amb} < 30\text{ }^{\circ}\text{C}$ ,  $RH < 60\%$


Moisture sensitivity level 4, acc. to J-STD-020.


## DRYING

In case of moisture absorption devices should be baked before soldering. Conditions see J-STD-020 or label. Devices taped on reel dry using recommended conditions 192 h at  $40\text{ }^{\circ}\text{C}$  (+  $5\text{ }^{\circ}\text{C}$ ),  $RH < 5\%$ .



**PACKAGE DIMENSIONS** in millimeters



**BLISTER TAPE DIMENSIONS** in millimeters



Drawing-No.: 9.700-5310.01-4

Issue: 2; 14.08.07

20690


Not indicated tolerances  $\pm 0.1$ 

Quantity per reel: 3000 pcs





**REEL DIMENSIONS** in millimeters



Drawing-No.: 9.800-5096.01-4  
Issue: 2; 26.04.10  
20875



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.