

Direct Water Cooled Wirewound Resistor



FEATURES

- Direct cooling without heatsink
- Excellent power / volume ratio
- Multi resistive element option
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

APPLICATIONS

- Filter resistor
- Snubber resistor
- Discharge resistor

DESIGN SUPPORT TOOLS

[click logo to get started](#)
3D
Models
Available

STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	POWER RATING P_n ⁽¹⁾ W	RESISTANCE RANGE Ω	TOLERANCE \pm %
DCRF 38 x 178	1500	0.56 to 4.7	5, 10 ⁽²⁾
DCRF 38 x 224	3000	1 to 9.1	5
DCRF 38 x 270	4500	1.5 to 15	5
DCRF 38 x 316	6000	2 to 20	5
DCRF 38 x 362	7500	2.4 to 24	5
DCRF 38 x 410	9000	3 to 27	5

Notes

⁽¹⁾ Water inlet temperature 65 °C with 40 % mono ethylene glycol, flow rate 8.33 l/min

⁽²⁾ 5 for value $\geq 1 \Omega$, 10 for value $< 1 \Omega$

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	RESISTOR CHARACTERISTICS
Temperature coefficient	ppm/°C	100 ppm/°C (typical)
Maximum working voltage	V	Up to 3600 V
Operating temperature range	°C	-55 to +120
Water conductivity	μ S/cm	< 2

GENERAL CHARACTERISTICS

Core	Ceramic, stainless steel
Winding	NiCr alloy (direct in water)
Hydraulic plugs	Stainless steel
Coating	None: ceramic nude
Ohmic values	E24 (for other values consult us)
Inductance	Refer to Inductance curves (see Fig. 3)
Cooling	Deionized water ⁽¹⁾ ; coolant mixtures up to 60 % mono ethylene glycol
Operating pressure	1 bar to 6 bars
Test pressure	15 bars
Flow	8.33 l/min to 16 l/min (see Fig. 2)
CTI index	> 600
Creeping distance	On request


GENERAL CHARACTERISTICS

Clearance distance	On request
Dielectric strength V_{RMS} (50 Hz / 1 min)	8000 V ⁽²⁾
Partial discharge	For free partial discharge version please consult us
Electrical connections	M4 rod (tightening 2 Nm max.)
Mounting	Minimum 5° angle from horizontal (see "Mounting Recommendation")
Overload	$2 \times P_n$ 60 s ($\theta_{65}^{\circ}C$ at 8.33 l/min)
Endurance	1200 h; P_n 30 s / 30 s; variation < 5 % (MCB laboratory condition)
Pressure drop	Refer to "Pressure Drop" curves (see Fig. 4)

Notes

- (1) Water conductivity must be permanently controlled to remain under 2 $\mu S/cm$.
The cooling mixture must remain homogeneous without any liquid or solid foreign element.
Use appropriate filter with regenerating mixed bed resin device
- (2) Resistor filled with deionized water (conductivity < 2 $\mu S/cm$)

DIMENSIONS in millimeters



TYPE	38 x 178	38 x 224	38 x 270	38 x 316	38 x 362	38 x 410
Water pipe fitting internal diameter	Ø 6.6 mini	Ø 6.6 mini	Ø 6.6 mini	Ø 6.6 mini	Ø 6.6 mini	Ø 6.6 mini
A	32	78	124	170	216	264
B +0.5 / -0	44	44	44	44	44	44
D max.	43	43	43	43	43	43
e	Ø M4	Ø M4	Ø M4	Ø M4	Ø M4	Ø M4
E	9	9	9	9	9	9
H max.	80	80	80	80	80	80
k	32	32	32	32	32	32
K	32	32	32	32	32	32
L max.	213	259	305	351	397	445
Ø	38	38	38	38	38	38
Q	G 3/8"	G 3/8"	G 3/8"	G 3/8"	G 3/8"	G 3/8"
U ± 6	178.8	224.8	270.8	316.8	362.8	410.8
V	35	35	35	35	35	35
W	34	34	34	34	34	34
X ± 6	182.8	228.8	274.8	320.8	366.8	414.8
Weight kg	0.77	0.89	1.01	1.13	1.26	1.38

POWER DISSIPATION




Fig. 1 - Power vs. Water Inlet Temperature
 $P_n = f(\text{Water Inlet Temperature})$, Flow Rate = 8.33 l/min

FLOW RATE




Fig. 2 - Power vs. Flow Rate
 $P_n = f(\text{Flow Rate})$, Water Inlet Temperature = 65 °C

INDUCTANCE




Fig. 3 - Inductance vs. Ohmic Value
 Maximum Inductance (may Vary for Particular Rated Values)

PRESSURE DROP





Fig. 4 - Pressure Drop vs. Flow Rate
 40 % of Mono Ethylene Glycol at 20 °C

MOUNTING RECOMMENDATION





ORDERING INFORMATION

DCRF	38 x 178	U56	± 10 %	XXX	BO12
MODEL	STYLE	RESISTANCE VALUE	TOLERANCE	CUSTOM DESIGN	PACKAGING
			± 5 % ± 10 %	Optional On request: special value, multiple resistor, etc.	

GLOBAL PART NUMBER INFORMATION

RESISTOR MARKING																	
D	C	R	F	3	8	1	7	8	0	R	5	6	K	B	8	7	9
1				2					3				4	5	6		
1		2		3			4		5			6					
PRODUCT TYPE		TYPE		RESISTANCE VALUE			TOLERANCE		PACKAGING			INDUSTRIALIZATION NUMBER					
DCRF		38178 38224 38270 38316 38362 38410		The first three digits are significant figures and the last specifies the number of zeros to follow, R designates decimal point. 4R7 = 4.7 Ω 0R56 = 0.56 Ω			J = 5 % K = 10 %		B = box Box quantity depends of model and size			3 specific digits (if applicable)					



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.