



Automotive Multilayer Chip Ferrite Beads



LINKS TO ADDITIONAL RESOURCES



White Paper

MECHANICAL SPECIFICATIONS

Solderability: per J-STD-002

Resistance to Solder Heat: 255 °C, 30 s max., 3x max. through reflow

Terminal Strength: 17.7 N force for 60 s

Flex: 0.079" [2 mm] mounted on 0.063" [1.6 mm] thick PC board

FEATURES

- 1.0 mm x 0.5 mm x 0.5 mm package
- Multilayer chip ferrite bead for high current filtering
- Wide variety of impedance values
- Extended current rating
- Multiple performance curves to target specific frequencies
- Silver (Ag) inner conductor with Cu / Ni / Sn electrode plating
- AEC-Q200 qualified
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

HALOGEN
FREE

GREEN
(5-2008)

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature: -55 °C to +125 °C

Thermal Shock: 1000 cycles, -55 °C (for 30 min ± 3 min) to +125 °C (for 30 min ± 3 min) with 20 s max. transition interval

Biased Humidity: 85 % RH at 85 °C, 1000 h at full rated current

STANDARD ELECTRICAL SPECIFICATIONS

PART NUMBER	Z ± 25 % AT 100 MHz (Ω)	DCR MAX. AT 25 °C (mΩ)	RATED DC CURRENT TYP. AT 85 °C ⁽¹⁾ (A)	Z _{pk} ⁽²⁾ (Ω)	F AT Z _{pk} ⁽³⁾ (MHz)	Z TYP. AT 100 MHz (Ω)	F AT Z _{DO} ⁽⁴⁾ (MHz)	XL / XR x OVER ⁽⁵⁾ (MHz)
IHLB0402ER100VHC11	10	18	3.1	19	1211	10	10 000	125
ILHB0402ER300VGP11	30	200	0.3	39	581	30	4500	36
ILHB0402ER300VHC41	30	50	1.7	58	174	30	> 10 000	138
ILHB0402ER300VHC42	30	35	2.2	57	1103	30	> 10 000	130
ILHB0402ERV300SS11	30	150	0.6	177	1329	30	5000	422
ILHB0402ER310VGP11	31	200	0.3	54	1118	30	> 10 000	125
ILHB0402ER330VSS11	33	400	0.3	759	811	31	5000	710
ILHB0402ER600VGP11	60	300	0.2	103	879	60	5500	116
ILHB0402ER600VHC41	60	75	1.5	103	952	61	9000	107
ILHB0402ER700VGP11	70	300	0.2	91	515	68	2921	43
ILHB0402ER700VHC3	70	100	0.8	111	700	70	3200	82
ILHB0402ER700VHC32	70	100	1.2	85	495	66	2297	31
ILHB0402ER750VSS11	75	300	0.6	433	664	75	3500	360
ILHB0402ER750VSS12	75	300	0.6	193	939	73	3200	208
IHLB0402ER800VHC11	80	38	2.3	128	597	79	1984	110
ILHB0402ER800VGP11	80	350	0.2	136	759	80	4000	107
ILHB0402ER800VGP12	80	350	0.2	120	630	75	2359	78
ILHB0402ER800VHC41	80	70	1.5	144	790	80	3800	122
IHLB0402ER121VHC11	120	50	2	186	551	110	1581	116
IHLB0402ER121VHF11	120	700	0.3	855	1018	128	5500	416
ILHB0402ER121VGP11	120	400	0.2	200	558	121	1905	111
ILHB0402ER121VGP13	120	400	0.2	154	451	122	1602	37
ILHB0402ER121VGP12	120	400	0.2	178	558	120	1957	76
ILHB0402ER121VHC3	120	130	0.7	184	566	120	1905	78
ILHB0402ER121VHC32	120	120	1	153	445	120	1783	38
ILHB0402ER121VHC41	120	90	1.3	206	664	116	2456	122
ILHB0402ER121VSS11	120	400	0.4	673	463	120	2100	302
ILHB0402ER121VSS12	120	400	0.4	317	700	120	2300	197
IHLB0402ER181VHF11	180	1000	0.1	540	891	160	3800	254



STANDARD ELECTRICAL SPECIFICATIONS

PART NUMBER	Z $\pm$ 25 % AT 100 MHz (Ω)	DCR MAX. AT 25 °C (m Ω)	RATED DC CURRENT TYP. AT 85 °C ⁽¹⁾ (A)	Z _{pk} ⁽²⁾ (Ω)	F AT Z _{pk} ⁽³⁾ (MHz)	Z TYP. AT 100 MHz (Ω)	F AT Z _{DO} ⁽⁴⁾ (MHz)	XL / XR x OVER ⁽⁵⁾ (MHz)
IHLB0402ER221VHF11	220	1000	0.25	1348	800	214	4200	390
IHLB0402ER221VHF12	220	500	0.3	431	811	195	2920	149
ILHB0402ER221VGP11	220	450	0.15	352	433	227	1175	104
ILHB0402ER221VGP12	220	500	0.1	261	350	210	729	32
ILHB0402ER221VHC3	220	180	0.6	304	379	220	890	66
ILHB0402ER221VHC32	220	180	0.8	272	327	217	790	36
ILHB0402ER221VHC41	220	160	0.9	362	451	225	1260	104
ILHB0402ER221VSS11	220	700	0.2	1066	323	211	1163	231
ILHB0402ER221VSS12	220	700	0.2	536	522	222	1581	185
ILHB0402ER241VGP11	240	500	0.2	358	410	244	1075	78
IHLB0402ER301VHF11	300	1000	0.1	566	581	307	2178	122
IHLB0402ER301VHF12	300	1100	0.1	868	811	300	2960	208
ILHB0402ER301VGP11	300	500	0.1	479	359	300	903	108
ILHB0402ER301VGP12	300	600	0.1	356	287	300	589	34
ILHB0402ER301VSS11	300	800	0.2	345	422	300	1178	159
ILHB0402ER421VGP11	420	600	0.1	585	271	420	580	91
ILHB0402ER421VGP12	420	800	0.1	486	241	417	476	32
ILHB0402ER421VSS11	420	1000	0.15	849	294	420	738	149
IHLB0402ER471VHF11	470	1300	0.1	1357	621	470	2237	219
ILHB0402ER501VGP11	500	800	0.1	712	254	521	551	90
IHLB0402ER601VHF11	600	1500	0.1	1122	589	615	1880	124
IHLB0402ER601VHF12	600	1600	0.1	1571	581	600	2037	211
IHLB0402ER601VHF13	600	1200	0.1	869	509	580	1856	40
ILHB0402ER601VGP11	600	900	0.1	818	211	614	400	90
ILHB0402ER601VGP12	600	900	0.1	867	235	626	463	83
ILHB0402ER601VGP13	600	900	0.1	707	203	616	374	34
ILHB0402ER601VHC3	600	340	0.45	709	192	595	327	60
ILHB0402ER601VHC32	600	340	0.45	671	185	614	298	29
ILHB0402ER601VSS11	600	1100	0.1	1202	258	595	597	145
ILHB0402ER751VGP11	750	1000	0.1	1066	192	775	379	96
IHLB0402ER102VHF11	1000	1800	0.05	1886	589	1000	1713	124
IHLB0402ER102VHF12	1000	1800	0.05	1369	374	1000	1059	37
ILHB0402ER102VGP11	1000	1200	0.1	1187	153	1000	228	80
ILHB0402ER102VGP12	1000	1200	0.1	1034	120	1000	157	32
ILHB0402ER102VSS11	1000	1200	0.1	1714	177	1025	302	119
IHLB0402ER152VHF11	1500	2200	0.05	3728	509	1550	1479	182
ILHB0402ER152VGP11	1500	1600	0.1	1745	139	1550	190	80
ILHB0402ER152VSS11	1500	1400	0.1	2235	149	1550	231	107
IHLB0402ER182VHF11	1800	2400	0.05	3738	350	1800	1018	153
ILHB0402ER182VGP11	1800	2000	0.05	2033	97	2038	125	65
ILHB0402ER182VSS11	1800	1800	0.05	2372	143	1768	197	96

Notes

- All test data is referenced to 25 °C ambient (unless otherwise indicated)
 - Operating temperature range: -55 °C to +125 °C
 - Storage condition: < 40 °C and < 70 % RH (in packaging)
 - The part temperature (ambient + temp. rise) should not exceed the maximum rating under worst case operating conditions. Circuit design, component placement, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application
- (1) Rated current is the DC current that causes a 40 °C temperature rise at 20 °C ambient
- (2) Z_{pk} = peak of impedance curve
- (3) F at Z_{pk} = frequency of Z_{pk}
- (4) F at Z_{DO} = frequency above 100 MHz where Z drops to nominal Z
- (5) XL / XR x over = crossover point for inductive reactance and resistance impedance



GLOBAL PART NUMBER

I L H B

PRODUCT FAMILY

0 4 0 2

SIZE

E R

PACKAGE
CODE

ER = tape and reel

3 0 1

INDUCTANCE
VALUE

121 = 120 Ω

V

IMPEDANCE
TOLERANCE


V = $\pm 25\%$

H C 1


APPLICATION

HCxx = high current
HFxx = high frequency
GPxx = general purpose
SSxx = signal specific

DIMENSIONS in inches [millimeters]















Dimensional outline















Typical pad layout







SIZE	A	B	C	D	E	F	G
0402	0.039 $\pm$ 0.006 [1.0 $\pm$ 0.15]	0.020 $\pm$ 0.006 [0.5 $\pm$ 0.15]	0.020 $\pm$ 0.006 [0.5 $\pm$ 0.15]	0.010 $\pm$ 0.004 [0.25 $\pm$ 0.10]	0.055 [1.4]	0.020 [0.5]	0.020 [0.5]







PERFORMANCE GRAPHS








PERFORMANCE GRAPHS








PERFORMANCE GRAPHS








PERFORMANCE GRAPHS








PERFORMANCE GRAPHS








PERFORMANCE GRAPHS






PERFORMANCE GRAPHS


PERFORMANCE GRAPHS


PERFORMANCE GRAPHS


PERFORMANCE GRAPHS


PERFORMANCE GRAPHS


PERFORMANCE GRAPHS




Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.