

Solid-Electrolyte TANTALEX™ Capacitors, Hermetically Sealed, Axial-Lead, CECC Approved



FEATURES

- Terminations: tin / lead (SnPb), 100 % tin (RoHS-compliant)
- Hermetically sealed metal case with plastic film insulation
- Extended capacitance range (type 749DX)
- High operational stability with both time and temperature
- Low leakage current
- Low dissipation factor
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



PERFORMANCE CHARACTERISTICS

Operating Temperature:

-55 °C to +85 °C (types CTS13)

-55 °C to +125 °C (types CTS1, 749DX)

SPECIFICATIONS

CECC	BS
30201-001	749DX 9073-N001 749DX
30201-002 CTS1	
30201-005 CTS13	
30201-029 749DX	

Note

* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details

APPLICATIONS

Performance and reliability has been proven in a wide range of applications such as: filtering, by-pass, coupling, energy storage, timing circuits.

CTS13	105	X0	040	A	2	P	E3
TYPE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT +85 °C	CASE CODE	STYLE NUMBER	PACKAGING	RoHS-COMPLIANT
Identifies the basic capacitor design CTS1 = CECC 30201-002 CTS13 = CECC 30201-005 749DX = CECC 30201-001 / CECC 30201-029	Expressed in picofarads. First two digits are significant. Third digit is the number of zeros following.	X0 = ± 20 % X9 = ± 10 % X5 = ± 5 % * * Special order	Expressed in volts. Where necessary, zeros precede the voltage rating to complete the 3 digit block 6R3 = 6.3 V	See Ratings and Case Codes table.	0 = bare case 2 = plastic-film insulation	See Tape and Reel Packaging	E3 = 100 % tin termination (RoHS-compliant) Blank = SnPb termination

DIMENSIONS in inches [millimeters]				
CASE CODE	$L_1 \pm 0.031$ [0.79]	J max.	D max.	LEAD DIAMETER + 10 %, - 0.05
A	0.286 [7.26]	0.402 [10.2]	0.141 [3.6]	0.020 [0.5]
B	0.474 [12.04]	0.590 [15.0]	0.192 [4.9]	0.020 [0.5]
C	0.686 [17.42]	0.807 [20.5]	0.295 [7.5]	0.025 [0.6]
D	0.786 [19.96]	0.945 [24.0]	0.364 [9.1]	0.025 [0.6]



RATINGS AND CASE CODES - TYPE CTS1							
C _R (μF)	RATED VOLTAGE U _R (+85 °C)						
	6.3 V	10 V	16 V	25 V	40 V	50 V	63 V
	CATEGORY VOLTAGE U _C (+125 °C)						
	4 V	6.3 V	10 V	13 V	25 V	33 V	40 V
0.10							A
0.12							A
0.15							A
0.18							A
0.22							A
0.27						A	A
0.33						A	A
0.39						A	A
0.47					A	A	A
0.56					A	A	A
0.68					A	A	A
0.82					A	A	B
1.0					A	A	B
1.2					A	B	B
1.5				A	B	B	B
1.8			A		B	B	B
2.2			A		B	B	B
2.7			A		B	B	B
3.3			A		B	B	B
3.9		A			B	B	B
4.7		A			B	B	C
5.6	A				B	C	C
6.8	A				B	C	C
8.2				B	C	C	C
10				B	C	C	C
12			B		C	C	D
15			B		C	C	D
18			B		C	C	D
22			B		C	D	
27		B		C	D		
33		B		C	D		
39	B		C		D		
47	B		C		D		
56	B		C	D			
68			C	D			
82		C	D				
100		C	D				
120	C		D				
150	C		D				
180		D					
220		D					
270	D						
330	D						



RATINGS AND CASE CODES - TYPE CTS13								
C _R (μF)	RATED VOLTAGE U _R (+85 °C)							
	6.3 V	10 V	16 V	20 V	25 V	40 V	50 V	63 V
0.10								A
0.12								A
0.15								A
0.18								A
0.22								A
0.27							A	A
0.33							A	A
0.39							A	A
0.47						A	A	A
0.56						A	A	A
0.68						A	A	A
0.82						A	A	B
1.0						A	A	B
1.2					A	A	B	B
1.5					A	B	B	B
1.8				A		B	B	B
2.2				A		B	B	B
2.7			A			B	B	B
3.3			A			B	B	B
3.9		A				B	B	B
4.7		A				B	B	C
5.6	A					B	C	C
6.8	A					B	C	C
8.2					B	C	C	C
10					B	C	C	C
12				B		C	C	D
15				B		C	C	D
18			B			C	C	D
22			B			C	D	
27		B			C	D		
33		B			C	D		
39	B			C		D		
47	B			C		D		
56	B		C		D			
68			C		D			
82		C		D				
100		C		D				
120	C		D					
150	C		D					
180		D						
220		D						
270	D							
330	D							



RATINGS AND CASE CODES - TYPE 749DX									
C _R (μF)	RATED VOLTAGE U _R (+85 °C)								
	6.3 V	10 V	16 V	20 V	25 V	35 V	40 V	50 V	63 V
	CATEGORY VOLTAGE U _C (+125 °C)								
	4 V	6.3 V	10 V	13 V	16 V	23 V	25 V	33 V	40 V
0.068									
0.10						A	A		A
0.12						A	A		A
0.15						A	A		A
0.18						A	A		A
0.22						A	A		A
0.27						A	A		A
0.33						A	A		A
0.39						A	A		A
0.47						A	A		A
0.56						A	A		A
0.68						A	A		A
0.82						A	A	A	B
1.0						A	A	A	B
1.2					A	B	B	B	B
1.5					A	B	B	B	B
1.8				A		B	B	B	B
2.2				A		B	B	B	B
2.7			A			B	B	B	B
3.3			A			B	B	B	B
3.9		A				B	B	B	B
4.7		A				B	B	B	C
5.6	A					B	B	C	C
6.8	A					B	B	C	C
8.2					B	C	C	C	C
10					B	C	C	C	C
12				B		C	C	C	D
15				B		C	C	C	D
18			B			C	C	C	D
22			B			C	C	D	
27		B			C	D	D		
33		B			C	D	D		
39		B		C		D	D		
47	B			C		D			
56	B		C		D	D			
68			C		D				
82		C		D					
100		C		D					
120		C	D						
150	C		D						
180	C	D							
220		D							
270	D								
330	D								



STANDARD RATINGS / EXTENDED RATINGS - CTS1						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
6.3 V_{DC} AT +85 °C; 4 V_{DC} AT +125 °C						
5.6	A	CTS1565(1)6R3A(2)(3)	1.0	6	10	
6.8	A	CTS1685(1)6R3A(2)(3)	1.0	6	10	
39	B	CTS1396(1)6R3B(2)(3)	2.3	6	5	
47	B	CTS1476(1)6R3B(2)(3)	2.8	6	5	
56	B	CTS1566(1)6R3B(2)(3)	3.4	6	5	
120	C	CTS1127(1)6R3C(2)(3)	7.2	6	2	
150	C	CTS1157(1)6R3C(2)(3)	9.0	6	2	
270	D	CTS1277(1)6R3D(2)(3)	16.2	6	1	
330	D	CTS1337(1)6R3D(2)(3)	19.8	8	1	
10 V_{DC} AT +85 °C; 6.3 V_{DC} AT +125 °C						
3.9	A	CTS1395(1)010A(2)(3)	1.0	6	10	
4.7	A	CTS1475(1)010A(2)(3)	1.0	6	10	
27	B	CTS1276(1)010B(2)(3)	2.7	6	5	
33	B	CTS1336(1)010B(2)(3)	3.3	6	5	
82	C	CTS1826(1)010C(2)(3)	8.2	6	2	
100	C	CTS1107(1)010C(2)(3)	10.0	6	2	
180	D	CTS1187(1)010D(2)(3)	18.0	6	1	
220	D	CTS1227(1)010D(2)(3)	22.0	8	1	
16 V_{DC} AT +85 °C; 10 V_{DC} AT +125 °C						
1.8	A	CTS1185(1)016A(2)(3)	1.0	6	10	
2.2	A	CTS1225(1)016A(2)(3)	1.0	6	10	
2.7	A	CTS1275(1)016A(2)(3)	1.0	6	10	
3.3	A	CTS1335(1)016A(2)(3)	1.0	6	10	
12	B	CTS1126(1)016B(2)(3)	1.9	6	5	
15	B	CTS1156(1)016B(2)(3)	2.4	6	5	
18	B	CTS1186(1)016B(2)(3)	2.9	6	5	
22	B	CTS1226(1)016B(2)(3)	3.5	6	5	
39	C	CTS1396(1)016C(2)(3)	6.2	6	2	
47	C	CTS1476(1)016C(2)(3)	7.5	6	2	
56	C	CTS1566(1)016C(2)(3)	9.0	6	2	
68	C	CTS1686(1)016C(2)(3)	10.9	6	2	
82	D	CTS1826(1)016D(2)(3)	13.1	6	1	
100	D	CTS1107(1)016D(2)(3)	16.0	6	1	
120	D	CTS1127(1)016D(2)(3)	19.2	8	1	
150	D	CTS1157(1)016D(2)(3)	24.0	8	1	
25 V_{DC} AT +85 °C; 16 V_{DC} AT +125 °C						
1.5	A	CTS1155(1)025A(2)(3)	1.0	6	10	
8.2	B	CTS1825(1)025B(2)(3)	2.1	6	5	
10	B	CTS1106(1)025B(2)(3)	2.5	6	5	
27	C	CTS1276(1)025C(2)(3)	6.8	6	2	
33	C	CTS1336(1)025C(2)(3)	8.3	6	2	
56	D	CTS1566(1)025D(2)(3)	14.0	6	1	
68	D	CTS1686(1)025D(2)(3)	17.0	6	1	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



STANDARD RATINGS / EXTENDED RATINGS - CTS1						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
40 V_{DC} AT +85 °C; 25 V_{DC} AT +125 °C						
0.47	A	CTS1474(1)040A(2)(3)	1.0	6	10	
0.56	A	CTS1564(1)040A(2)(3)	1.0	6	10	
0.68	A	CTS1684(1)040A(2)(3)	1.0	6	10	
0.82	A	CTS1824(1)040A(2)(3)	1.0	6	10	
1.0	A	CTS1105(1)040A(2)(3)	1.0	6	10	
1.2	A	CTS1125(1)040A(2)(3)	1.0	6	10	
1.5	B	CTS1155(1)040B(2)(3)	1.0	6	5	
1.8	B	CTS1185(1)040B(2)(3)	1.0	6	5	
2.2	B	CTS1225(1)040B(2)(3)	1.0	6	5	
2.7	B	CTS1275(1)040B(2)(3)	1.1	6	5	
3.3	B	CTS1335(1)040B(2)(3)	1.3	6	5	
3.9	B	CTS1395(1)040B(2)(3)	1.6	6	5	
4.7	B	CTS1475(1)040B(2)(3)	1.9	6	5	
5.6	B	CTS1565(1)040B(2)(3)	2.2	6	5	
6.8	B	CTS1685(1)040B(2)(3)	2.7	6	5	
8.2	C	CTS1825(1)040C(2)(3)	3.3	6	2	
10	C	CTS1106(1)040C(2)(3)	4.0	6	2	
12	C	CTS1126(1)040C(2)(3)	4.8	6	2	
15	C	CTS1156(1)040C(2)(3)	6.0	6	2	
18	C	CTS1186(1)040C(2)(3)	7.2	6	2	
22	C	CTS1226(1)040C(2)(3)	8.8	6	2	
27	D	CTS1276(1)040D(2)(3)	10.8	6	1	
33	D	CTS1336(1)040D(2)(3)	13.2	6	1	
39	D	CTS1396(1)040D(2)(3)	15.6	6	1	
47	D	CTS1476(1)040D(2)(3)	18.8	6	1	
50 V_{DC} AT +85 °C; 33 V_{DC} AT +125 °C						
0.27	A	CTS1274(1)050A(2)(3)	1.0	6	n/a	
0.33	A	CTS1334(1)050A(2)(3)	1.0	6	10	
0.39	A	CTS1394(1)050A(2)(3)	1.0	6	10	
0.47	A	CTS1474(1)050A(2)(3)	1.0	6	10	
0.56	A	CTS1564(1)050A(2)(3)	1.0	6	10	
0.68	A	CTS1684(1)050A(2)(3)	1.0	6	10	
0.82	A	CTS1824(1)050A(2)(3)	1.0	6	10	
1.0	A	CTS1105(1)050A(2)(3)	1.0	6	10	
1.2	B	CTS1125(1)050B(2)(3)	1.0	6	5	
1.5	B	CTS1155(1)050B(2)(3)	1.0	6	5	
1.8	B	CTS1185(1)050B(2)(3)	1.0	6	5	
2.2	B	CTS1225(1)050B(2)(3)	1.1	6	5	
2.7	B	CTS1275(1)050B(2)(3)	1.4	6	5	
3.3	B	CTS1335(1)050B(2)(3)	1.7	6	5	
3.9	B	CTS1395(1)050B(2)(3)	2.0	6	5	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



STANDARD RATINGS / EXTENDED RATINGS - CTS1						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
50 V_{DC} AT +85 °C; 33 V_{DC} AT +125 °C						
4.7	B	CTS1475(1)050B(2)(3)	2.4	6	5	
5.6	C	CTS1565(1)050C(2)(3)	2.8	6	2	
6.8	C	CTS1685(1)050C(2)(3)	3.4	6	2	
8.2	C	CTS1825(1)050C(2)(3)	4.1	6	2	
10	C	CTS1106(1)050C(2)(3)	5.0	6	2	
12	C	CTS1126(1)050C(2)(3)	6.0	6	2	
15	C	CTS1156(1)050C(2)(3)	7.5	6	2	
18	C	CTS1186(1)050C(2)(3)	9.0	6	2	
22	D	CTS1226(1)050D(2)(3)	11.0	6	1	
63 V_{DC} AT +85 °C; 40 V_{DC} AT +125 °C						
0.10	A	CTS1104(1)063A(2)(3)	1.0	6	n/a	
0.12	A	CTS1124(1)063A(2)(3)	1.0	6	n/a	
0.15	A	CTS1154(1)063A(2)(3)	1.0	6	n/a	
0.18	A	CTS1184(1)063A(2)(3)	1.0	6	n/a	
0.22	A	CTS1224(1)063A(2)(3)	1.0	6	n/a	
0.27	A	CTS1274(1)063A(2)(3)	1.0	6	n/a	
0.33	A	CTS1334(1)063A(2)(3)	1.0	6	10	
0.39	A	CTS1394(1)063A(2)(3)	1.0	6	10	
0.47	A	CTS1474(1)063A(2)(3)	1.0	6	10	
0.56	A	CTS1564(1)063A(2)(3)	1.0	6	10	
0.68	A	CTS1684(1)063A(2)(3)	1.0	6	10	
0.82	B	CTS1824(1)063B(2)(3)	1.0	6	5	
1.0	B	CTS1105(1)063B(2)(3)	1.0	6	5	
1.2	B	CTS1125(1)063B(2)(3)	1.0	6	5	
1.5	B	CTS1155(1)063B(2)(3)	1.0	6	5	
1.8	B	CTS1185(1)063B(2)(3)	1.1	6	5	
2.2	B	CTS1225(1)063B(2)(3)	1.4	6	5	
2.7	B	CTS1275(1)063B(2)(3)	1.7	6	5	
3.3	B	CTS1335(1)063B(2)(3)	2.1	6	5	
3.9	B	CTS1395(1)063B(2)(3)	2.5	6	5	
4.7	C	CTS1475(1)063C(2)(3)	3.0	6	2	
5.6	C	CTS1565(1)063C(2)(3)	3.5	6	2	
6.8	C	CTS1685(1)063C(2)(3)	4.3	6	2	
8.2	C	CTS1825(1)063C(2)(3)	5.2	6	2	
10	C	CTS1106(1)063C(2)(3)	6.3	6	2	
12	D	CTS1126(1)063D(2)(3)	7.6	6	1	
15	D	CTS1156(1)063D(2)(3)	9.5	6	1	
18	D	CTS1186(1)063D(2)(3)	11.3	6	1	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



STANDARD RATINGS / EXTENDED RATINGS - CTS13						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
6.3 V_{DC} AT +85 °C						
5.6	A	CTS13565(1)6R3A(2)(3)	1.0	6	10	
6.8	A	CTS13685(1)6R3A(2)(3)	1.0	6	10	
39	B	CTS13396(1)6R3B(2)(3)	2.3	6	5	
47	B	CTS13476(1)6R3B(2)(3)	2.8	6	5	
56	B	CTS13566(1)6R3B(2)(3)	3.4	6	5	
120	C	CTS13127(1)6R3C(2)(3)	7.2	6	2	
150	C	CTS13157(1)6R3C(2)(3)	9.0	6	2	
270	D	CTS13277(1)6R3D(2)(3)	16.2	6	1	
330	D	CTS13337(1)6R3D(2)(3)	19.8	8	1	
10 V_{DC} AT +85 °C						
3.9	A	CTS13395(1)010A(2)(3)	1.0	6	10	
4.7	A	CTS13475(1)010A(2)(3)	1.0	6	10	
27	B	CTS13276(1)010B(2)(3)	2.7	6	5	
33	B	CTS13336(1)010B(2)(3)	3.3	6	5	
82	C	CTS13826(1)010C(2)(3)	8.2	6	2	
100	C	CTS13107(1)010C(2)(3)	10.0	6	2	
180	D	CTS13187(1)010D(2)(3)	18.0	6	1	
220	D	CTS13227(1)010D(2)(3)	22.0	8	1	
16 V_{DC} AT +85 °C						
2.7	A	CTS13275(1)016A(2)(3)	1.0	6	10	
3.3	A	CTS13335(1)016A(2)(3)	1.0	6	10	
18	B	CTS13186(1)016B(2)(3)	2.9	6	5	
22	B	CTS13226(1)016B(2)(3)	3.5	6	5	
56	C	CTS13566(1)016C(2)(3)	9.0	6	2	
68	C	CTS13686(1)016C(2)(3)	10.9	6	2	
120	D	CTS13127(1)016D(2)(3)	19.2	8	1	
150	D	CTS13157(1)016D(2)(3)	24.0	8	1	
20 V_{DC} AT +85 °C						
1.8	A	CTS13185(1)020A(2)(3)	1.0	6	10	
2.2	A	CTS13225(1)020A(2)(3)	1.0	6	10	
12	B	CTS13126(1)020B(2)(3)	2.4	6	5	
15	B	CTS13156(1)020B(2)(3)	3.0	6	5	
39	C	CTS13396(1)020C(2)(3)	7.8	6	2	
47	C	CTS13476(1)020C(2)(3)	9.4	6	2	
82	D	CTS13826(1)020D(2)(3)	16.4	6	1	
100	D	CTS13107(1)020D(2)(3)	20.0	8	1	
25 V_{DC} AT +85 °C						
1.2	A	CTS13125(1)025A(2)(3)	1.0	6	10	
1.5	A	CTS13155(1)025A(2)(3)	1.0	6	10	
8.2	B	CTS13825(1)025B(2)(3)	2.1	6	5	
10	B	CTS13106(1)025B(2)(3)	2.5	6	5	
27	C	CTS13276(1)025C(2)(3)	6.8	6	2	
33	C	CTS13336(1)025C(2)(3)	8.3	6	2	
56	D	CTS13566(1)025D(2)(3)	14.0	6	1	
68	D	CTS13686(1)025D(2)(3)	17.0	6	1	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



STANDARD RATINGS / EXTENDED RATINGS - CTS13						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
40 V_{DC} AT +85 °C						
0.47	A	CTS13474(1)040A(2)(3)	1.0	6	10	
0.56	A	CTS13564(1)040A(2)(3)	1.0	6	10	
0.68	A	CTS13684(1)040A(2)(3)	1.0	6	10	
0.82	A	CTS13824(1)040A(2)(3)	1.0	6	10	
1.0	A	CTS13105(1)040A(2)(3)	1.0	6	10	
1.2	A	CTS13125(1)040A(2)(3)	1.0	6	10	
1.5	B	CTS13155(1)040B(2)(3)	1.0	6	5	
1.8	B	CTS13185(1)040B(2)(3)	1.0	6	5	
2.2	B	CTS13225(1)040B(2)(3)	1.0	6	5	
2.7	B	CTS13275(1)040B(2)(3)	1.1	6	5	
3.3	B	CTS13335(1)040B(2)(3)	1.3	6	5	
3.9	B	CTS13395(1)040B(2)(3)	1.6	6	5	
4.7	B	CTS13475(1)040B(2)(3)	1.9	6	5	
5.6	B	CTS13565(1)040B(2)(3)	2.2	6	5	
6.8	B	CTS13685(1)040B(2)(3)	2.7	6	5	
8.2	C	CTS13825(1)040C(2)(3)	3.3	6	2	
10	C	CTS13106(1)040C(2)(3)	4.0	6	2	
12	C	CTS13126(1)040C(2)(3)	4.8	6	2	
15	C	CTS13156(1)040C(2)(3)	6.0	6	2	
18	C	CTS13186(1)040C(2)(3)	7.2	6	2	
22	C	CTS13226(1)040C(2)(3)	8.8	6	2	
27	D	CTS13276(1)040D(2)(3)	10.8	6	1	
33	D	CTS13336(1)040D(2)(3)	13.2	6	1	
39	D	CTS13396(1)040D(2)(3)	15.6	6	1	
47	D	CTS13476(1)040D(2)(3)	18.8	6	1	
50 V_{DC} AT +85 °C						
0.27	A	CTS13274(1)050A(2)(3)	1.0	6	n/a	
0.33	A	CTS13334(1)050A(2)(3)	1.0	6	10	
0.39	A	CTS13394(1)050A(2)(3)	1.0	6	10	
0.47	A	CTS13474(1)050A(2)(3)	1.0	6	10	
0.56	A	CTS13564(1)050A(2)(3)	1.0	6	10	
0.68	A	CTS13684(1)050A(2)(3)	1.0	6	10	
0.82	A	CTS13824(1)050A(2)(3)	1.0	6	10	
1.0	A	CTS13105(1)050A(2)(3)	1.0	6	10	
1.2	B	CTS13125(1)050B(2)(3)	1.0	6	5	
1.5	B	CTS13155(1)050B(2)(3)	1.0	6	5	
1.8	B	CTS13185(1)050B(2)(3)	1.0	6	5	
2.2	B	CTS13225(1)050B(2)(3)	1.1	6	5	
2.7	B	CTS13275(1)050B(2)(3)	1.4	6	5	
3.3	B	CTS13335(1)050B(2)(3)	1.7	6	5	
3.9	B	CTS13395(1)050B(2)(3)	2.0	6	5	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



STANDARD RATINGS / EXTENDED RATINGS - CTS13						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
50 V_{DC} AT +85 °C						
4.7	B	CTS13475(1)050B(2)(3)	2.4	6	5	
5.6	C	CTS13565(1)050C(2)(3)	2.8	6	2	
6.8	C	CTS13685(1)050C(2)(3)	3.4	6	2	
8.2	C	CTS13825(1)050C(2)(3)	4.1	6	2	
10	C	CTS13106(1)050C(2)(3)	5.0	6	2	
12	C	CTS13126(1)050C(2)(3)	6.0	6	2	
15	C	CTS13156(1)050C(2)(3)	7.5	6	2	
18	C	CTS13186(1)050C(2)(3)	9.0	6	2	
22	D	CTS13226(1)050D(2)(3)	11.0	6	1	
63 V_{DC} AT +85 °C						
0.10	A	CTS13104(1)063A(2)(3)	1.0	6	n/a	
0.12	A	CTS13124(1)063A(2)(3)	1.0	6	n/a	
0.15	A	CTS13154(1)063A(2)(3)	1.0	6	n/a	
0.18	A	CTS13184(1)063A(2)(3)	1.0	6	n/a	
0.22	A	CTS13224(1)063A(2)(3)	1.0	6	n/a	
0.27	A	CTS13274(1)063A(2)(3)	1.0	6	n/a	
0.33	A	CTS13334(1)063A(2)(3)	1.0	6	10	
0.39	A	CTS13394(1)063A(2)(3)	1.0	6	10	
0.47	A	CTS13474(1)063A(2)(3)	1.0	6	10	
0.56	A	CTS13564(1)063A(2)(3)	1.0	6	10	
0.68	A	CTS13684(1)063A(2)(3)	1.0	6	10	
0.82	B	CTS13824(1)063B(2)(3)	1.0	6	5	
1.0	B	CTS13105(1)063B(2)(3)	1.0	6	5	
1.2	B	CTS13125(1)063B(2)(3)	1.0	6	5	
1.5	B	CTS13155(1)063B(2)(3)	1.0	6	5	
1.8	B	CTS13185(1)063B(2)(3)	1.1	6	5	
2.2	B	CTS13225(1)063B(2)(3)	1.4	6	5	
2.7	B	CTS13275(1)063B(2)(3)	1.7	6	5	
3.3	B	CTS13335(1)063B(2)(3)	2.1	6	5	
3.9	B	CTS13395(1)063B(2)(3)	2.5	6	5	
4.7	C	CTS13475(1)063C(2)(3)	3.0	6	2	
5.6	C	CTS13565(1)063C(2)(3)	3.5	6	2	
6.8	C	CTS13685(1)063C(2)(3)	4.3	6	2	
8.2	C	CTS13825(1)063C(2)(3)	5.2	6	2	
10	C	CTS13106(1)063C(2)(3)	6.3	6	2	
12	D	CTS13126(1)063D(2)(3)	7.6	6	1	
15	D	CTS13156(1)063D(2)(3)	9.5	6	1	
18	D	CTS13186(1)063D(2)(3)	11.3	6	1	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



STANDARD RATINGS / EXTENDED RATINGS - 749DX						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
6.3 V_{DC} AT +85 °C; 4 V_{DC} AT +125 °C						
5.6	A	749DX565(1)6R3A(2)(3)	1.0	6	10	
6.8	A	749DX685(1)6R3A(2)(3)	1.0	6	10	
47	B	749DX476(1)6R3B(2)(3)	2.8	6	5	
56	B	749DX566(1)6R3B(2)(3)	3.4	6	5	
150	C	749DX157(1)6R3C(2)(3)	9.0	8	2	
180	C	749DX187(1)6R3C(2)(3)	10.8	8	2	
270	D	749DX277(1)6R3D(2)(3)	16.2	8	1	
330	D	749DX337(1)6R3D(2)(3)	19.8	8	1	
10 V_{DC} AT +85 °C; 6.3 V_{DC} AT +125 °C						
3.9	A	749DX395(1)010A(2)(3)	1.0	6	10	
4.7	A	749DX475(1)010A(2)(3)	1.0	6	10	
27	B	749DX276(1)010B(2)(3)	2.7	6	5	
33	B	749DX336(1)010B(2)(3)	3.3	6	5	
39	B	749DX396(1)010B(2)(3)	3.9	6	5	
82	C	749DX826(1)010C(2)(3)	8.2	6	2	
100	C	749DX107(1)010C(2)(3)	10.0	6	2	
120	C	749DX127(1)010C(2)(3)	12.0	8	2	
180	D	749DX187(1)010D(2)(3)	18.0	8	1	
220	D	749DX227(1)010D(2)(3)	22.0	8	1	
16 V_{DC} AT +85 °C; 10 V_{DC} AT +125 °C						
2.7	A	749DX275(1)016A(2)(3)	1.0	6	10	
3.3	A	749DX335(1)016A(2)(3)	1.0	6	10	
18	B	749DX186(1)016B(2)(3)	2.9	6	5	
22	B	749DX226(1)016B(2)(3)	3.5	6	5	
56	C	749DX566(1)016C(2)(3)	9.0	6	2	
68	C	749DX686(1)016C(2)(3)	10.9	6	2	
120	D	749DX127(1)016D(2)(3)	19.2	8	1	
150	D	749DX157(1)016D(2)(3)	24.0	8	1	
20 V_{DC} AT +85 °C; 13 V_{DC} AT +125 °C						
1.8	A	749DX185(1)020A(2)(3)	1.0	6	10	
2.2	A	749DX225(1)020A(2)(3)	1.0	6	10	
12	B	749DX126(1)020B(2)(3)	2.4	6	5	
15	B	749DX156(1)020B(2)(3)	3.0	6	5	
39	C	749DX396(1)020C(2)(3)	7.8	6	2	
47	C	749DX476(1)020C(2)(3)	9.4	6	2	
82	D	749DX826(1)020D(2)(3)	16.4	6	1	
100	D	749DX107(1)020D(2)(3)	20.0	6	1	
25 V_{DC} AT +85 °C; 16 V_{DC} AT +125 °C						
1.2	A	749DX125(1)025A(2)(3)	1.0	6	10	
1.5	A	749DX155(1)025A(2)(3)	1.0	6	10	
8.2	B	749DX825(1)025B(2)(3)	2.1	6	5	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



STANDARD RATINGS / EXTENDED RATINGS - 749DX						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
25 V_{DC} AT +85 °C; 16 V_{DC} AT +125 °C						
10	B	749DX106(1)025B(2)(3)	2.5	6	5	
27	C	749DX276(1)025C(2)(3)	6.8	6	2	
33	C	749DX336(1)025C(2)(3)	8.3	6	2	
56	D	749DX566(1)025D(2)(3)	14.0	6	1	
68	D	749DX686(1)025D(2)(3)	17.0	6	1	
35 V_{DC} AT +85 °C; 23 V_{DC} AT +125 °C						
0.10	A	749DX104(1)035A(2)(3)	1.0	6	n/a	
0.12	A	749DX124(1)035A(2)(3)	1.0	6	n/a	
0.15	A	749DX154(1)035A(2)(3)	1.0	6	n/a	
0.18	A	749DX184(1)035A(2)(3)	1.0	6	n/a	
0.22	A	749DX224(1)035A(2)(3)	1.0	6	n/a	
0.27	A	749DX274(1)035A(2)(3)	1.0	6	n/a	
0.33	A	749DX334(1)035A(2)(3)	1.0	6	n/a	
0.39	A	749DX394(1)035A(2)(3)	1.0	6	n/a	
0.47	A	749DX474(1)035A(2)(3)	1.0	6	n/a	
0.56	A	749DX564(1)035A(2)(3)	1.0	6	n/a	
0.68	A	749DX684(1)035A(2)(3)	1.0	6	10	
0.82	A	749DX824(1)035A(2)(3)	1.0	6	10	
1.0	A	749DX105(1)035A(2)(3)	1.0	6	10	
1.2	B	749DX125(1)035B(2)(3)	1.0	6	5	
1.5	B	749DX155(1)035B(2)(3)	1.0	6	5	
1.8	B	749DX185(1)035B(2)(3)	1.0	6	5	
2.2	B	749DX225(1)035B(2)(3)	1.0	6	5	
2.7	B	749DX275(1)035B(2)(3)	1.0	6	5	
3.3	B	749DX335(1)035B(2)(3)	1.2	6	5	
3.9	B	749DX395(1)035B(2)(3)	1.4	6	5	
4.7	B	749DX475(1)035B(2)(3)	1.6	6	5	
5.6	B	749DX565(1)035B(2)(3)	2.0	6	5	
6.8	B	749DX685(1)035B(2)(3)	2.4	6	5	
8.2	C	749DX825(1)035C(2)(3)	2.9	6	2	
10	C	749DX106(1)035C(2)(3)	3.5	6	2	
12	C	749DX126(1)035C(2)(3)	4.2	6	2	
15	C	749DX156(1)035C(2)(3)	5.3	6	2	
18	C	749DX186(1)035C(2)(3)	6.3	6	2	
22	C	749DX226(1)035C(2)(3)	7.7	6	2	
27	D	749DX276(1)035D(2)(3)	9.5	6	1	
33	D	749DX336(1)035D(2)(3)	11.6	6	1	
39	D	749DX396(1)035D(2)(3)	13.7	6	1	
47	D	749DX476(1)035D(2)(3)	16.5	6	1	
56	D	749DX566(1)035D(2)(3)	19.6	6	1	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



STANDARD RATINGS / EXTENDED RATINGS - 749DX						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C 100 kHz (Ω)	
40 V_{DC} AT +85 °C; 25 V_{DC} AT +125 °C						
0.10	A	749DX104(1)040A(2)(3)	1.0	6	n/a	
0.12	A	749DX124(1)040A(2)(3)	1.0	6	n/a	
0.15	A	749DX154(1)040A(2)(3)	1.0	6	n/a	
0.18	A	749DX184(1)040A(2)(3)	1.0	6	n/a	
0.22	A	749DX224(1)040A(2)(3)	1.0	6	n/a	
0.27	A	749DX274(1)040A(2)(3)	1.0	6	n/a	
0.33	A	749DX334(1)040A(2)(3)	1.0	6	n/a	
0.39	A	749DX394(1)040A(2)(3)	1.0	6	n/a	
0.47	A	749DX474(1)040A(2)(3)	1.0	6	n/a	
0.56	A	749DX564(1)040A(2)(3)	1.0	6	n/a	
0.68	A	749DX684(1)040A(2)(3)	1.0	6	10	
0.82	A	749DX824(1)040A(2)(3)	1.0	6	10	
1.0	A	749DX105(1)040A(2)(3)	1.0	6	10	
1.2	B	749DX125(1)040B(2)(3)	1.0	6	5	
1.5	B	749DX155(1)040B(2)(3)	1.0	6	5	
1.8	B	749DX185(1)040B(2)(3)	1.0	6	5	
2.2	B	749DX225(1)040B(2)(3)	1.0	6	5	
2.7	B	749DX275(1)040B(2)(3)	1.1	6	5	
3.3	B	749DX335(1)040B(2)(3)	1.3	6	5	
3.9	B	749DX395(1)040B(2)(3)	1.6	6	5	
4.7	B	749DX475(1)040B(2)(3)	1.9	6	5	
5.6	B	749DX565(1)040B(2)(3)	2.2	6	5	
6.8	B	749DX685(1)040B(2)(3)	2.7	6	5	
8.2	C	749DX825(1)040C(2)(3)	3.3	6	2	
10	C	749DX106(1)040C(2)(3)	4.0	6	2	
12	C	749DX126(1)040C(2)(3)	4.8	6	2	
15	C	749DX156(1)040C(2)(3)	6.0	6	2	
18	C	749DX186(1)040C(2)(3)	7.2	6	2	
22	C	749DX226(1)040C(2)(3)	8.8	6	2	
27	D	749DX276(1)040D(2)(3)	10.8	6	1	
33	D	749DX336(1)040D(2)(3)	13.2	6	1	
39	D	749DX396(1)040D(2)(3)	15.6	6	1	
50 V_{DC} AT +85 °C; 33 V_{DC} AT +125 °C						
0.82	A	749DX824(1)050A(2)(3)	1.0	6	10	
1.0	A	749DX105(1)050A(2)(3)	1.0	6	10	
1.2	B	749DX125(1)050B(2)(3)	1.0	6	5	
1.5	B	749DX155(1)050B(2)(3)	1.0	6	5	
1.8	B	749DX185(1)050B(2)(3)	1.0	6	5	
2.2	B	749DX225(1)050B(2)(3)	1.1	6	5	
2.7	B	749DX275(1)050B(2)(3)	1.4	6	5	
3.3	B	749DX335(1)050B(2)(3)	1.7	6	5	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code







STANDARD RATINGS / EXTENDED RATINGS - 749DX						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DCL AT +25 °C (μ A)	MAX. DF AT +25 °C 120 Hz (%)	MAX. IMPEDANCE AT +25 °C	
50 V _{DC} AT +85 °C; 33 V _{DC} AT +125 °C						
3.9	B	749DX395(1)050B(2)(3)	2.0	6	5	
4.7	B	749DX475(1)050B(2)(3)	2.4	6	5	
5.6	C	749DX565(1)050C(2)(3)	2.8	6	2	
6.8	C	749DX685(1)050C(2)(3)	3.4	6	2	
8.2	C	749DX825(1)050C(2)(3)	4.1	6	2	
10	C	749DX106(1)050C(2)(3)	5.0	6	2	
12	C	749DX126(1)050C(2)(3)	6.0	6	2	
15	C	749DX156(1)050C(2)(3)	7.5	6	2	
18	C	749DX186(1)050C(2)(3)	9.0	6	2	
22	D	749DX226(1)050D(2)(3)	11.0	6	1	
63 V _{DC} AT +85 °C; 40 V _{DC} AT +125 °C						
0.10	A	749DX104(1)063A(2)(3)	1.0	6	n/a	
0.12	A	749DX124(1)063A(2)(3)	1.0	6	n/a	
0.15	A	749DX154(1)063A(2)(3)	1.0	6	n/a	
0.18	A	749DX184(1)063A(2)(3)	1.0	6	n/a	
0.22	A	749DX224(1)063A(2)(3)	1.0	6	n/a	
0.27	A	749DX274(1)063A(2)(3)	1.0	6	n/a	
0.33	A	749DX334(1)063A(2)(3)	1.0	6	n/a	
0.39	A	749DX394(1)063A(2)(3)	1.0	6	n/a	
0.47	A	749DX474(1)063A(2)(3)	1.0	6	n/a	
0.56	A	749DX564(1)063A(2)(3)	1.0	6	n/a	
0.68	A	749DX684(1)063A(2)(3)	1.0	6	10	
0.82	B	749DX824(1)063B(2)(3)	1.0	6	5	
1.0	B	749DX105(1)063B(2)(3)	1.0	6	5	
1.2	B	749DX125(1)063B(2)(3)	1.0	6	5	
1.5	B	749DX155(1)063B(2)(3)	1.0	6	5	
1.8	B	749DX185(1)063B(2)(3)	1.1	6	5	
2.2	B	749DX225(1)063B(2)(3)	1.4	6	5	
2.7	B	749DX275(1)063B(2)(3)	1.7	6	5	
3.3	B	749DX335(1)063B(2)(3)	2.1	6	5	
3.9	B	749DX395(1)063B(2)(3)	2.5	6	5	
4.7	C	749DX475(1)063C(2)(3)	3.0	6	2	
5.6	C	749DX565(1)063C(2)(3)	3.5	6	2	
6.8	C	749DX685(1)063C(2)(3)	4.3	6	2	
8.2	C	749DX825(1)063C(2)(3)	5.2	6	2	
10	C	749DX106(1)063C(2)(3)	6.3	6	2	
12	D	749DX126(1)063D(2)(3)	7.6	6	1	
15	D	749DX156(1)063D(2)(3)	9.5	6	1	
18	D	749DX186(1)063D(2)(3)	11.3	6	1	

Note

- Part number definitions:
 - Capacitance tolerance code: X5, X9, X0
 - Style number: 0 or 2
 - Packaging code



TYPICAL CURVES RIPPLE VOLTAGE AT +25 °C



PRODUCT INFORMATION	
Mounting of Through Hole Components	www.vishay.com/doc?40108
Solid Tantalum Capacitors (With MnO ₂ Electrolyte) Voltage Derating	www.vishay.com/doc?40246
SELECTOR GUIDES	
Quick Reference Guide	www.vishay.com/doc?40037
Selector Guide	www.vishay.com/doc?49054
Parameter Comparison Guide	www.vishay.com/doc?40033
FAQ	
Frequently Asked Questions	www.vishay.com/doc?40110



PERFORMANCE CHARACTERISTICS

1. Operating Temperature:

-55 °C to +85 °C with rated DC voltage UR applied, +85 °C to +125 °C with linear voltage derating to category voltage UC (only for types CTS1, 749DX).

2. Capacitance and Tolerance:

Capacitance measured at 100 Hz and +25 °C shall be within the specified tolerance limits of the nominal rating. Capacitance measurement shall be made by means of a polarized capacitance bridge. The polarizing voltage shall be of 2.2 V. The maximum voltage applied during measurements shall be 1.0 VRMS at 100 Hz and +25 °C.

3. Reverse Voltage:

These capacitors are capable of withstanding peak voltage in the reverse direction equal to: 15 % of the rated DC voltage at +25 °C, 5 % of the rated DC voltage at +85 °C.

4. Surge Voltage:

Table 1

Table with 3 columns: PRODUCT TYPE, SURGE VOLTAGE AT +85 °C, SURGE VOLTAGE AT +125 °C. Rows for CTS13 and 749DX / CTS1.

Capacitors shall withstand the surge voltage applied in series with a 1000 W resistor, at the rate of 1.5 min on, 5.5 min off, for 1000 successive test cycles at +85 °C or at +125 °C. After test, dissipation factor and leakage current shall meet the initial requirements at +25 °C (see below), capacitance change shall not exceed ± 10 % of initial value at +25 °C.

5. Leakage Current:

Rated voltage UR shall be applied to capacitors during five minutes with a resistor of 1000 W in series with each capacitor, before making DC leakage current measurements. The leakage current shall not exceed the following limits:

Table 2

Table with 2 columns: TEMPERATURE, CTS1 / CTS13 / 749DX. Rows for +25 °C, +85 °C, +125 °C.

6. Dissipation Factor:

The dissipation factor, when measured at 100 Hz, shall not exceed the values below:

Table 3

Table with 5 columns: TEMP., CTS1 / CTS13 (CRUR ≤ 1900, CRUR > 1900), 749DX (CR ≤ 100, CR > 100). Rows for -55 °C, +25 °C, +85 °C, +125 °C (1).

Note

(1) Not applicable for CTS13

7. Stability at Low and High Temperature:

Capacitance change with temperature shall not exceed the limits of the following table, leakage current and dissipation factor shall be within the limits specified in Tables 2 and 3.

Table 4

Table with 2 columns: TEMPERATURE, CTS1 / CTS13 / 749DX. Rows for -55 °C, +85 °C, +125 °C (1).

Note

(1) Not applicable for CTS13

8. Impedance:

The impedance measured at 100 kHz and 25 °C shall not exceed the following values:

Table 5

Table with 2 columns: CASE CODE, Z (W) (1). Rows for A, B, C, D.

Note

(1) Not applicable for CR ≤ 0.68 µF

9. Life Test:

After 2000 h at +85 °C with rated DC voltage applied, or after 2000 h at +125 °C with category DC voltage applied (for types CTS1, 749DX only) capacitors shall meet the requirements in Table 6.

Table 6

Table with 4 columns: PRODUCT TYPE, CAPACITANCE CHANGE, DISSIPATION FACTOR, DC LEAKAGE CURRENT. Row for CTS1, CTS13, 749DX.



PERFORMANCE CHARACTERISTICS (Continued)

10. Humidity Test:

After 56 days (1350 h) at +40 °C, 90 % to 95 % of relative humidity (per IEC 68-2-3) with no voltage applied, capacitors shall meet the requirements in Table 7 below.

Table 7

Table with 2 columns: Parameter (Capacitance Change, DC Leakage Current, Dissipation Factor) and Requirement (Within ± 3 % of initial value, etc.)

Table 8

Table with 2 columns: Parameter (Capacitance Change, DC Leakage Current, Dissipation Factor) and Requirement (Within ± 5 % of initial value, etc.)

Typical values of charge-discharge current (per above test conditions).

Table with 2 columns: Rated Voltage UR (V) and Charge-Discharge Current (A). Rows include values from 6.3V to 63V.

11. Insulation Test:

For capacitors with insulating sleeves, a DC voltage of 100 V shall be applied for one minute between the case of the capacitor and a metal "V" block in intimate contact with the insulating sleeve.

12. Lead Pull Test:

Leads shall withstand the following test (IEC 68-2-2): tensile stress of 5N (cases A and B) or 10N (cases C and D) for 10 s in any direction

- One bend in each direction
Two consecutive rotations of 180°

GUIDE TO APPLICATION

1. AC Ripple Current:

The maximum allowable ripple current shall be determined from the formula:

IRMS = sqrt(P / RESR)

where,

P = power dissipation in W at +25 °C as given below

RESR = the capacitor equivalent series resistance at the specified frequency.

2. AC Ripple Voltage:

The maximum allowable ripple voltage shall be determined from the formula:

VRMS = sqrt(P / RESR) * Z

where,

Z = the capacitor impedance at the specified frequency.

The calculations are summarized on the graphs in table "Typical Curves Ripple Voltage at +25 °C" giving the maximum available ripple voltage as a function of frequency.

However, the sum of the peak AC voltage plus the DC voltage shall not exceed the rated DC voltage at +85 °C of the capacitor. The sum of the negative peak AC voltage plus the DC voltage shall not allow a voltage reversal exceeding 15 % of the rated DC voltage.

3. AC Ripple Current or Voltage Derating Factor:

If these capacitors are to be operated at temperatures above +25 °C, the permissible RMS ripple current or voltage shall be calculated using the derating factors in the table below:

Table with 2 columns: Temperature and Derating Factor. Rows include +25 °C (1.0), +55 °C (0.8), +85 °C (0.6), +125 °C (0.4).


4. Power Dissipation:

Power dissipation will be affected by the heat sinking capability of the mounting surface. Non-sinusoidal ripple current may produce heating effects which differ from those shown in the following table.

Table with 2 columns: Case Code and Power Dissipation at +25 °C (W). Rows include A (0.115), B (0.145), C (0.185), D (0.225).

TAPE AND REEL PACKAGING

Meets EIA standard RS-296


STANDARD PACKAGING QUANTITY AND DIMENSIONS in millimeters

CASE SIZE	REEL AND AMMO S	REEL PACK					AMMO PACK			BULK
		OPTION P		OPTION R		QTY PER REEL	OPTION G		QTY PER BOX	QTY PER PACK
		B	C MAX.	B	C MAX.		B	C MAX.		
A	5.0 ± 0.3	63 ± 2	78	53 ± 2	68	1000	53 ± 2	68	500	100
B	5.0 ± 0.3	63 ± 2	78	53 ± 2	68	1000	53 ± 2	68	500	75
C	10.0 ± 0.3	63 ± 2	78	63 ± 2	78	500	53 ± 2	68	250	50
D	10.0 ± 0.3	63 ± 2	78	63 ± 2	78	500	53 ± 2	68	250	25
PACKAGING CODE		P		R			G			B

MARKING

Capacitors shall be marked with Vishay Sprague marking (circled 2); the type number; rated capacitance and tolerance (with a letter code, if different from $\pm 20\%$, $K = \pm 10\%$; $J = \pm 5\%$); rated DC voltage at $+85^\circ\text{C}$ and the date code of manufacture.

Capacitors shall be marked on one end with a "plus" sign (+) to identify the positive terminal.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.