


Hermetic, 50 mil Pitch, Leadless Thin Film Chip Resistor, Surface Mount Network



Vishay Dale Thin film offers a four terminal hermetic leadless chip carrier package with precision matched pair elements. The network features tight ratio tolerance and close tracking over a 100 Ω to 100 kΩ resistance range. For custom schematics and values contact applications engineering.

FEATURES

- True hermetic construction
- Exceptional stability and performance characteristics ratio stability ($\Delta R \pm 0.015\%$ at 70 °C for 2000 h)
- Nickel barrier terminations
- Military/aerospace
- Hermetically sealed
- Compliant to RoHS Directive 2002/95/EC
- Halogen-free according to IEC 61249-2-21 definition




Note

* Pb containing terminations are not RoHS compliant, exemptions may apply

TYPICAL PERFORMANCE

	ABSOLUTE	TRACKING
TCR	25	5
	ABSOLUTE	RATIO
TOL.	0.1	0.05

SCHEMATIC



STANDARD ELECTRICAL SPECIFICATIONS		
TEST	SPECIFICATIONS	CONDITIONS
Material	Passivated nichrome	-
Pin/Lead Number	4	-
Resistance Range	100 Ω to 100 kΩ	-
TCR: Absolute	± 25 ppm/°C (standard)	- 55 °C to + 125 °C
TCR: Tracking	± 2 ppm/°C (typical < 1 ppm /°C equal values)	- 55 °C to + 125 °C
Tolerance: Absolute	$\pm 0.1\%$ to $\pm 1.0\%$	+ 25 °C
Tolerance: Ratio	$\pm 0.05\%$ to $\pm 0.1\%$	+ 25 °C
Power Rating: Resistor	250 mW (per element)	Maximum at + 70 °C
Power Rating: Package	1000 mW	Maximum at + 70 °C
Stability: Absolute	$\Delta R \pm 0.05\%$	2000 h at + 70 °C
Stability: Ratio	$\Delta R \pm 0.015\%$	2000 h at + 70 °C
Voltage Coefficient	< 0.1 ppm/V	-
Working Voltage	100 V max. not to exceed $\sqrt{P \times R}$	-
Operating Temperature Range	- 55 °C to + 125 °C	-
Storage Temperature Range	- 55 °C to + 150 °C	-
Noise	< - 30 dB	-
Thermal EMF	0.08 μV/°C	-
Shelf Life Stability: Absolute	$\Delta R \pm 0.01\%$	1 year at + 25 °C
Shelf Life Stability: Ratio	$\Delta R \pm 0.002\%$	1 year at + 25 °C

DIMENSIONS in inches and millimeters			
<p style="text-align: center;">BOTTOM VIEW</p>	DIMENSION	INCHES	MILLIMETERS
	A	0.155	3.937
	B	0.080	2.032
	C	0.225	5.715
	D	0.025 (typical)	0.635
	E	0.040	1.016
	F	0.070	1.778
	G	0.050	1.27

MECHANICAL SPECIFICATIONS	
Resistive Element	Passivated nichrome
Substrate Material	Alumina
Body	Ceramic
Terminals	Gold over nickel
Marking Resistance to Solvents	Per MIL-PRF-83401
Tin Lead Option	Sn63
Lead (Pb)-free Option	96.5 % Sn, 3.0 % Ag, 0.5 % Cu
Tin Lead and Lead (Pb)-free	Hot solder dip

GLOBAL PART NUMBER INFORMATION												
New Global Part Numbering: MPHK1003BUF												
	M	P	H	K	1	0	0	3	B	U	F	
	M	P	H	T	K	1	0	0	3	A	U	F
GLOBAL MODEL (3 or 4 digits)	TCR CHARACTERISTIC		RESISTANCE		TOLERANCE AND RATIO TOLERANCE		PACKAGING					
MPH (Tin lead)	E = 25 ppm/°C H = 50 ppm/°C K = 100 ppm/°C		First 3 digits are significant figures and the last digit specifies the number of zeros to follow. Example: 1001 = 1K 1002 = 10K		Abs. Tol. Ratio A = 0.1 % 0.05 % B = 0.1 % 0.1 % C = 0.25 % 0.1 % D = 0.5 % 0.1 % F = 1 % 0.5 %		TAPE AND REEL T0 = 100 min., 100 mult T1 = 1000 min., 1000 mult T3 = 300 min., 300 mult T5 = 500 min., 500 mult TF = Full reel 2500 TS = 100 min., 1 mult UF = TUBED					
MPHT (Lead (Pb)-free) (e1)												
Historical Part Number example: MPHE1001B (for reference purposes only)												
MPH	E		1001		B							
SERIES	TCR CHARACTERISTIC		RESISTANCE		TOLERANCE AND RATIO TOLERANCE							



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.