

P-Channel 20 V (D-S) MOSFET with Schottky Diode

| MOSFET PRODUCT SUMMARY | | | |
|------------------------|------------------------------------|--------------------|-----------------------|
| V _{DS} (V) | R _{DS(on)} (Ω) | I _D (A) | Q _g (Typ.) |
| - 20 | 0.105 at V _{GS} = - 4.5 V | - 4 ^a | 4.7 nC |
| | 0.143 at V _{GS} = - 2.5 V | - 3.8 | |
| | 0.188 at V _{GS} = - 1.8 V | - 3 | |

| SCHOTTKY PRODUCT SUMMARY | | |
|--------------------------|---|--------------------|
| V _{KA} (V) | V _f (V) Diode Forward Voltage | I _F (A) |
| 20 | 0.46 at 0.5 A | 1 |

FEATURES



- Halogen-free According to IEC 61249-2-21 Definition
- LITTLE FOOT® Plus Schottky Power MOSFET
- Compliant to RoHS Directive 2002/95/EC



RoHS
COMPLIANT
HALOGEN
FREE
Available

APPLICATIONS

- Charging Switch for Portable Devices
- With Integrated Low V_f Trench Schottky Diode



P-Channel MOSFET

Ordering Information: Si5853DDC-T1-E3 (Lead (Pb)-free)
Si5853DDC-T1-GE3 (Lead (Pb)-free and Halogen-free)

| ABSOLUTE MAXIMUM RATINGS T _A = 25 °C, unless otherwise noted | | | | | | |
|---|-----------------------------------|------------------------|-----------------------|---|-----------------------|--|
| Parameter | Symbol | Limit | Unit | | | |
| Drain-Source Voltage (MOSFET) | V _{DS} | - 20 | V | | | |
| Reverse Voltage (Schottky) | V _{KA} | 20 | | | | |
| Gate-Source Voltage (MOSFET) | V _{GS} | ± 8 | | | | |
| Continuous Drain Current (T _J = 150 °C) (MOSFET) | I _D | T _C = 25 °C | - 4 ^a | A | | |
| | | T _C = 70 °C | - 3.5 | | | |
| | | T _A = 25 °C | - 2.9 ^{b, c} | | | |
| | | T _A = 70 °C | - 2.3 ^{b, c} | | | |
| Pulsed Drain Current (MOSFET) | I _{DM} | - 10 | W | | | |
| Continuous Source Current (MOSFET Diode Conduction) | I _S | T _C = 25 °C | | | - 2.6 | |
| | | T _A = 25 °C | | | - 1.1 ^{b, c} | |
| Average Forward Current (Schottky) | I _F | 1 | W | | | |
| Pulsed Forward Current (Schottky) | I _{FM} | 3 | | | | |
| Maximum Power Dissipation (MOSFET) | P _D | T _C = 25 °C | | | 3.1 | |
| | | T _C = 70 °C | | | 2 | |
| | | T _A = 25 °C | | | 1.3 ^{b, c} | |
| | | T _A = 70 °C | | | 0.8 ^{b, c} | |
| Maximum Power Dissipation (Schottky) | P _D | T _C = 25 °C | | | 2.5 | |
| | | T _C = 70 °C | 1.6 | | | |
| | | T _A = 25 °C | 1.2 | | | |
| | | T _A = 70 °C | 0.76 | | | |
| Operating Junction and Storage Temperature Range | T _J , T _{stg} | - 55 to 150 | °C | | | |
| Soldering Recommendation (Peak Temperature) ^{d, e} | | 260 | | | | |

THERMAL RESISTANCE RATINGS

| Parameter | Symbol | Typical | Maximum | Unit |
|---|------------|---------|---------|------|
| Maximum Junction-to-Ambient (MOSFET) ^{b, c, f} | R_{thJA} | 77 | 95 | °C/W |
| Maximum Junction-to-Foot (Drain) (MOSFET) | R_{thJF} | 33 | 40 | |
| Maximum Junction-to-Ambient (Schottky) ^{b, c, g} | R_{thJA} | 85 | 105 | |
| Maximum Junction-to-Foot (Drain) (Schottky) | R_{thJF} | 40 | 50 | |

Notes:

- Package limited.
- Surface mounted on FR4 board.
- $t \leq 5$ s.
- See Solder Profile (www.vishay.com/doc?73257). The ChipFET is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.
- Rework conditions: manual soldering with a soldering iron is not recommended for leadless components.
- Maximum under steady state conditions for MOSFETs is 130 °C/W.
- Maximum under steady state conditions for Schottky is 125 °C/W.

SPECIFICATIONS $T_J = 25$ °C, unless otherwise noted

| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
|---|------------------------|--|------|-------|-----------|----------|
| Static | | | | | | |
| Drain-Source Breakdown Voltage | V_{DS} | $V_{GS} = 0$ V, $I_D = -250$ μ A | -20 | | | V |
| V_{DS} Temperature Coefficient | $\Delta V_{DS/TJ}$ | $I_D = -250$ μ A | | -13 | | mV/°C |
| $V_{GS(th)}$ Temperature Coefficient | $\Delta V_{GS(th)/TJ}$ | | 2.4 | | | |
| Gate-Source Threshold Voltage | $V_{GS(th)}$ | $V_{DS} = V_{GS}$, $I_D = -250$ μ A | -0.4 | | -1 | V |
| Gate-Body Leakage | I_{GSS} | $V_{DS} = 0$ V, $V_{GS} = \pm 8$ V | | | ± 100 | nA |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS} = -20$ V, $V_{GS} = 0$ V | | | -1 | μ A |
| | | $V_{DS} = -20$ V, $V_{GS} = 0$ V, $T_J = 85$ °C | | | -10 | |
| On-State Drain Current ^a | $I_{D(on)}$ | $V_{DS} \leq -5$ V, $V_{GS} = -4.5$ V | -10 | | | A |
| Drain-Source On-State Resistance ^a | $R_{DS(on)}$ | $V_{GS} = -4.5$ V, $I_D = -2.9$ A | | 0.085 | 0.105 | Ω |
| | | $V_{GS} = -2.5$ V, $I_D = -2.5$ A | | 0.117 | 0.143 | |
| | | $V_{GS} = -1.8$ V, $I_D = -1.5$ A | | 0.155 | 0.188 | |
| Forward Transconductance ^a | g_{fs} | $V_{DS} = -10$ V, $I_D = -2.9$ A | | 7 | | S |
| Dynamic^b | | | | | | |
| Input Capacitance | C_{iss} | $V_{DS} = -10$ V, $V_{GS} = 0$ V, $f = 1$ MHz | | 320 | | pF |
| Output Capacitance | C_{oss} | | 60 | | | |
| Reverse Transfer Capacitance | C_{rss} | | 47 | | | |
| Total Gate Charge | Q_g | $V_{DS} = -10$ V, $V_{GS} = -8$ V, $I_D = -2.9$ A | | 7.9 | 12 | nC |
| | | $V_{DS} = -10$ V, $V_{GS} = -4.5$ V, $I_D = -2.9$ A | | 4.7 | 7.1 | |
| Q_{gs} | | | 0.65 | | | |
| Q_{gd} | | | 1.35 | | | |
| Gate Resistance | R_g | $f = 1$ MHz | | 6.5 | | Ω |
| Turn-On Delay Time | $t_{d(on)}$ | $V_{DD} = -10$ V, $R_L = 4.4$ Ω $I_D \cong -2.3$ A, $V_{GEN} = -4.5$ V, $R_g = 1$ Ω | | 15 | 25 | ns |
| Rise Time | t_r | | | 17 | 30 | |
| Turn-Off Delay Time | $t_{d(off)}$ | | | 21 | 30 | |
| Fall Time | t_f | | | 10 | 15 | |
| Turn-On Delay Time | $t_{d(on)}$ | $V_{DD} = -10$ V, $R_L = 4.4$ Ω $I_D \cong -2.3$ A, $V_{GEN} = -8$ V, $R_g = 1$ Ω | | 5 | 10 | |
| Rise Time | t_r | | | 10 | 15 | |
| Turn-Off Delay Time | $t_{d(off)}$ | | | 20 | 30 | |
| Fall Time | t_f | | | 10 | 15 | |



| SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted | | | | | | |
|---|----------|--|------|--------|-------|------|
| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
| Drain-Source Body Diode Characteristics | | | | | | |
| Continuous Source-Drain Diode Current | I_S | $T_C = 25\text{ }^\circ\text{C}$ | | | - 2.6 | A |
| Pulse Diode Forward Current | I_{SM} | | | | - 10 | |
| Body Diode Voltage | V_{SD} | $I_S = - 2.3\text{ A}$, $V_{GS} = 0\text{ V}$ | | - 0.85 | - 1.2 | V |
| Body Diode Reverse Recovery Time | t_{rr} | $I_F = - 2.3\text{ A}$ $di/dt = 100\text{ A}/\mu\text{s}$ $T_J = 25\text{ }^\circ\text{C}$ | | 15 | 30 | ns |
| Body Diode Reverse Recovery Charge | Q_{rr} | | | 9 | 20 | nC |
| Reverse Recovery Fall Time | t_a | | | 10 | | ns |
| Reverse Recovery Rise Time | t_b | | | 5 | | |







Notes:

- a. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.
- b. Guaranteed by design, not subject to production testing.


| SCHOTTKY SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted | | | | | | |
|--|----------|---|------|--------|-------|------|
| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
| Forward Voltage Drop | V_F | $I_F = 0.5\text{ A}$ | | 0.381 | 0.46 | V |
| | | $I_F = 1\text{ A}$ | | 0.468 | 0.560 | |
| | | $I_F = 1\text{ A}$, $T_J = 125\text{ }^\circ\text{C}$ | | 0.44 | 0.53 | |
| Maximum Reverse Leakage Current | I_{rm} | $V_r = 5\text{ V}$ | | 0.0081 | 0.080 | mA |
| | | $V_r = 5\text{ V}$, $T_J = 85\text{ }^\circ\text{C}$ | | 0.4 | 4 | |
| | | $V_r = 5\text{ V}$, $T_J = 125\text{ }^\circ\text{C}$ | | 2.8 | 28 | |
| | | $V_r = 20\text{ V}$ | | 0.0093 | 0.09 | |
| | | $V_r = 20\text{ V}$, $T_J = 85\text{ }^\circ\text{C}$ | | 0.45 | 4.5 | |
| | | $V_r = 20\text{ V}$, $T_J = 125\text{ }^\circ\text{C}$ | | 3.2 | 32 | |
| Junction Capacitance | C_T | $V_r = 10\text{ V}$ | | 30 | | pF |

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


MOSFET TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




MOSFET TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage





Single Pulse Power, Junction-to-Ambient



* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified


Safe Operating Area, Junction-to-Ambient

MOSFET TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

MOSFET TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Foot


SCHOTTKY TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Reverse Current vs. Junction Temperature




Forward Voltage Drop



SCHOTTKY TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted






Normalized Thermal Transient Impedance, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Foot

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?68979.

1206-8 ChipFET®



NOTES:


1. All dimensions are in millimeters.
2. Mold gate burrs shall not exceed 0.13 mm per side.
3. Leadframe to molded body offset is horizontal and vertical shall not exceed 0.08 mm.

4. Dimensions exclusive of mold gate burrs.

5. No mold flash allowed on the top and bottom lead surface.

| Dim | MILLIMETERS | | | INCHES | | |
|---|-------------|------|-------|------------|-------|--------|
| | Min | Nom | Max | Min | Nom | Max |
| A | 1.00 | — | 1.10 | 0.039 | — | 0.043 |
| b | 0.25 | 0.30 | 0.35 | 0.010 | 0.012 | 0.014 |
| c | 0.1 | 0.15 | 0.20 | 0.004 | 0.006 | 0.008 |
| c1 | 0 | — | 0.038 | 0 | — | 0.0015 |
| D | 2.95 | 3.05 | 3.10 | 0.116 | 0.120 | 0.122 |
| E | 1.825 | 1.90 | 1.975 | 0.072 | 0.075 | 0.078 |
| E₁ | 1.55 | 1.65 | 1.70 | 0.061 | 0.065 | 0.067 |
| e | 0.65 BSC | | | 0.0256 BSC | | |
| L | 0.28 | — | 0.42 | 0.011 | — | 0.017 |
| S | 0.55 BSC | | | 0.022 BSC | | |
| α | 5°Nom | | | 5°Nom | | |
| ECN: C-03528—Rev. F, 19-Jan-04 DWG: 5547 | | | | | | |

RECOMMENDED MINIMUM PADS FOR 1206-8 ChipFET®



Recommended Minimum Pads
Dimensions in Inches/(mm)

[Return to Index](#)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.