

## N-Channel 80 V (D-S) 175 °C MOSFET

### DESCRIPTION


The attached SPICE model describes the typical electrical characteristics of the n-channel vertical DMOS. The subcircuit model is extracted and optimized over the - 55 °C to 125 °C temperature ranges under the pulsed 0 V to 10 V gate drive. The saturated output impedance is best fit at the gate bias near the threshold voltage.

A novel gate-to-drain feedback capacitance network is used to model the gate charge characteristics while avoiding convergence difficulties of the switched  $C_{gd}$  model. All model parameter values are optimized to provide a best fit to the measured electrical data and are not intended as an exact physical interpretation of the device.

### CHARACTERISTICS

- N-Channel Vertical DMOS
- Macro Model (Subcircuit Model)
- Level 3 MOS
- Apply for both Linear and Switching Application
- Accurate over the - 55 °C to + 125 °C Temperature Range
- Model the Gate Charge

### SUBCIRCUIT MODEL SCHEMATIC



### Note

- This document is intended as a SPICE modeling guideline and does not constitute a commercial product datasheet. Designers should refer to the appropriate datasheet of the same number for guaranteed specification limits.









SPECIFICATIONS ( $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise noted)					
PARAMETER	SYMBOL	TEST CONDITIONS	SIMULATED DATA	MEASURED DATA	UNIT
<b>Static</b>					
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$	3.4	-	V
On-State Drain Current <sup>a</sup>	$I_{D(on)}$	$V_{DS} = 5\ \text{V}, V_{GS} = 10\ \text{V}$	304	-	A
Drain-Source On-State Resistance <sup>a</sup>	$R_{DS(on)}$	$V_{GS} = 10\ \text{V}, I_D = 40\ \text{A}$	0.013	0.013	$\Omega$
		$V_{GS} = 10\ \text{V}, I_D = 40\ \text{A}, T_J = 125\text{ }^\circ\text{C}$	0.022	-	
		$V_{GS} = 10\ \text{V}, I_D = 40\ \text{A}, T_J = 175\text{ }^\circ\text{C}$	0.026	-	
Forward Transconductance <sup>a</sup>	$g_{fs}$	$V_{DS} = 15\ \text{V}, I_D = 40\ \text{A}$	49	45	S
Diode Forward Voltage	$V_{SD}$	$I_S = 40\ \text{A}, V_{GS} = 0\ \text{V}$	0.91	1	V
<b>Dynamic<sup>b</sup></b>					
Input Capacitance	$C_{iss}$	$V_{DS} = 25\ \text{V}, V_{GS} = 0\ \text{V}, f = 1\ \text{MHz}$	2091	1960	pF
Output Capacitance	$C_{oss}$		438	370	
Reverse Transfer Capacitance	$C_{rss}$		248	200	
Total Gate Charge	$Q_g$	$V_{DS} = 40\ \text{V}, V_{GS} = 10\ \text{V}, I_D = 40\ \text{A}$	39	42	nC
Gate-Source Charge	$Q_{gs}$		7	7	
Gate-Drain Charge	$Q_{gd}$		13	13	
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = 40\ \text{V}, R_L = 1\ \Omega$ $I_D = 40\ \text{A}, V_{GEN} = 10\ \text{V}, R_g = 2.5\ \Omega$	19	12	ns
Rise Time	$t_r$		29	52	
Turn-Off Delay Time	$t_{d(off)}$		31	25	
Fall Time	$t_f$		40	10	
Source-Drain Reverse Recovery Time	$t_{rr}$		$I_F = 40\ \text{A}, di/dt = 100\ \text{A}/\mu\text{s}$	38	

**Notes**

- a. Pulse test; pulse width  $\leq 300\ \mu\text{s}$ , duty cycle  $\leq 2\ \%$ .  
b. Guaranteed by design, not subject to production testing.



## COMPARISON OF MODEL WITH MEASURED DATA ( $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise noted)



### Note

- Dots and squares represent measured data.