

Optocoupler

CERTIFICATE FI 28155



Our ref. 272222

Product	Optocoupler
Type	4N25., 4N26., 4N27., 4N28., 4N35., 4N36., 4N37., 4N38., CNY17-1., CNY17-2., CNY17-3., CNY17-4
Trade mark	
Certificate Holder	Vishay Semiconductor GmbH, Theresienstrasse 2 D-74072 HEILBRONN, GERMANY
Manufacturer	Everlight Electronic Co. Ltd No.25.Lane 76, Sec.3 Chung Yang Road,Tucheng, 23671 Taipei, TAIWAN.
Technical information	Evaluated to be without internal clearance/creepage distance for reinforced insulation up to a required withstand voltage of 1.5 kV (OVC II max. 150 V) and 2.5 kV (OVC II max. 300 V). PD 2, 2000 m, operating temperature 110 °C.
The product has been tested according to standard(s)	EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 EN 60065:2002 + A1:2006 + A11:2008 + A2:2010 + A12:2011,
Validity	This certificate is valid until 20 August 2018 unless the standard in question has been amended or superseded with significant changes in requirements, in which case, SGS Fimko has the right to shorten the validity of the certificate based on the legislation of the European Union. This certificate includes the right to use the FI and SGS FI marks under the condition that changes (if any) will be checked at SGS Fimko before the product is brought onto market and that the conditions for FI certification are met.
Date of the test result	20 August 2013
Signature	 Timo Silonsaari Specialist

This certificate has 1 appendix



This certificate is issued by the company under its General Conditions for Certification Services accessible at <http://www.sgs.fi/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Fimko Ltd.	Särkinientie 3 P.O.Box 30 FI-00211 Helsinki, Finland
	t. +358 9 696 361 f. +358 9 692 5474 www.sgs.fi
Business ID 0978538-5	Member of the SGS Group (SGS SA)



Appendix to Certificate: 28155

Manufacturing site(s) Everlight Electronic Co. Ltd
 No.2135 Zhong Shan North Rd, Wujiang Economy Development
 Zone, Songling Town, Jiangsu
 P.R.China

Additional information

Molding compounds:
 Internal : EME-1100 by Chang Chun Plastic
 External : EC15-15 by Chang Chun Plastic

Maximum required withstand voltage is 2.5 kV which represents OVC II max. 250 Vrms (reinforced insulation). Maximum required withstand voltage is 4.0 kV which represents OVC III max. 300 Vrms (basic / supplementary insulation). Internal clearance and creepage distance between input and output is 5.6 mm. Min.

External clearance and creepage distance between input and output is 7.8 mm. Min.

The optocouplers were subjected to an electric strength test between input and output of 2830 Vac/1 min (basic / supplementary: OVC III max. 300 V) and 3000 Vac. / 1 min (reinforced: OVC II max. 250 V).

Distance through insulation between input and output is more than 0.4 mm, measured a minimum of 1.10 mm.

After judgement from case to case, the optocouplers may bridge functional, basic, supplementary and/or reinforced insulation, or may be used in other environments, provided that the ratings are not exceeded in normal operation.

Is based on test 272222-3

This certificate is issued by the company under its General Conditions for Certification Services accessible at <http://www.sgs.fi/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.