



Phase Control Thyristors (Stud Version), 80 A



TO-94 (TO-209AC)

FEATURES

- Hermetic glass-metal seal
- International standard case TO-94 (TO-209AC)
- Designed and qualified for industrial level
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

TYPICAL APPLICATIONS

- DC motor controls
- Controlled DC power supplies
- AC controllers

PRIMARY CHARACTERISTICS

| | |
|-----------------------|----------------------|
| $I_{T(AV)}$ | 80 A |
| V_{DRM}/V_{RRM} | 400 V, 800 V, 1200 V |
| V_{TM} | 1.60 V |
| I_{GT} | 120 mA |
| T_J | -40 °C to +125 °C |
| Package | TO-94 (TO-209AC) |
| Circuit configuration | Single SCR |

MAJOR RATINGS AND CHARACTERISTICS

| PARAMETER | TEST CONDITIONS | VALUES | UNITS |
|-------------------|-----------------|-------------|-------------------|
| $I_{T(AV)}$ | | 80 | A |
| | T_C | 85 | °C |
| $I_{T(RMS)}$ | | 125 | A |
| I_{TSM} | 50 Hz | 1900 | |
| | 60 Hz | 1990 | |
| I^2t | 50 Hz | 18 | kA ² s |
| | 60 Hz | 16 | |
| V_{DRM}/V_{RRM} | | 400 to 1200 | V |
| t_q | Typical | 110 | μs |
| T_J | | -40 to +125 | °C |

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS

| TYPE NUMBER | VOLTAGE CODE | V_{DRM}/V_{RRM} , MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE V | V_{RSM} , MAXIMUM NON-REPETITIVE PEAK VOLTAGE V | I_{DRM}/I_{RRM} MAXIMUM AT $T_J = 125\text{ °C}$ mA |
|----------------------|--------------|--|--|--|
| VS-80RIA VS-81RIA | 40 | 400 | 500 | 15 |
| | 80 | 800 | 900 | |
| | 120 | 1200 | 1300 | |

**ABSOLUTE MAXIMUM RATINGS**

| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
|--|---------------|---|--------|--------------------|
| Maximum average on-state current at case temperature | $I_{T(AV)}$ | 180° conduction, half sine wave | 80 | A |
| | | | 85 | °C |
| Maximum RMS on-state current | $I_{T(RMS)}$ | DC at 75 °C case temperature | 125 | |
| Maximum peak, one-cycle non-repetitive surge current | I_{TSM} | <div> <div> <div>t = 10 ms</div> <div>No voltage reapplied</div> </div> <div> <div>t = 8.3 ms</div> <div>100 % V_{RRM} reapplied</div> </div> </div> <div>Sinusoidal half wave, initial $T_J = T_J$ maximum</div> | 1900 | A |
| | | | 1990 | |
| | | | 1600 | |
| | | | 1675 | |
| Maximum I^2t for fusing | I^2t | <div> <div> <div>t = 10 ms</div> <div>No voltage</div> </div> <div> <div>t = 8.3 ms</div> <div>100 % V_{RRM} reapplied</div> </div> </div> <div>Sinusoidal half wave, initial $T_J = T_J$ maximum</div> | 18 | kA ² s |
| | | | 16 | |
| | | | 12.7 | |
| | | | 11.7 | |
| Maximum $I^2\sqrt{t}$ for fusing | $I^2\sqrt{t}$ | t = 0.1 ms to 10 ms, no voltage reapplied | 180.5 | kA ² √s |
| Low level value of threshold voltage | $V_{T(TO)1}$ | (16.7 % $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$), $T_J = T_J$ maximum | 0.99 | V |
| High level value of threshold voltage | $V_{T(TO)2}$ | ($I > \pi \times I_{T(AV)}$), $T_J = T_J$ maximum | 1.13 | |
| Low level value of on-state slope resistance | r_{t1} | (16.7 % $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$), $T_J = T_J$ maximum | 2.29 | mΩ |
| High level value of on-state slope resistance | r_{t2} | ($I > \pi \times I_{T(AV)}$), $T_J = T_J$ maximum | 1.84 | |
| Maximum on-state voltage | V_{TM} | $I_{pk} = 250$ A, $T_J = 25$ °C, $t_p = 10$ ms sine pulse | 1.60 | V |
| Maximum holding current | I_H | $T_J = 25$ °C, anode supply 12 V resistive load | 200 | mA |
| Typical latching current | I_L | | 400 | |

SWITCHING

| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
|--|---------|--|--------|-------|
| Maximum non-repetitive rate of rise of turned-on current | di/dt | $T_J = 125$ °C, $V_d = \text{Rated } V_{DRM}$, $I_{TM} = 2 \times di/dt$ snubber 0.2 μF, 15 Ω, gate pulse: 20 V, 65 Ω, $t_p = 6$ μs, $t_r = 0.5$ μs Per JEDEC standard RS-397, 5.2.2.6. | 300 | A/μs |
| Typical delay time | t_d | Gate pulse: 10 V, 15 Ω source, $t_p = 6$ μs, $t_r = 0.1$ μs, $V_d = \text{Rated } V_{DRM}$, $I_{TM} = 50$ Adc, $T_J = 25$ °C | 1 | μs |
| Typical turn-off time | t_q | $I_{TM} = 50$ A, $T_J = T_J$ maximum, $di/dt = -5$ A/μs, $V_R = 50$ V, $dV/dt = 20$ V/μs, gate bias: 0 V 25 Ω, $t_p = 500$ μs | 110 | |

BLOCKING

| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
|--|-----------------------|--|--------|-------|
| Maximum critical rate of rise of off-state voltage | dV/dt | $T_J = 125$ °C exponential to 67 % rated V_{DRM} | 500 | V/μs |
| Maximum peak reverse and off-state leakage current | I_{RRM} , I_{DRM} | $T_J = 125$ °C rated V_{DRM}/V_{RRM} applied | 15 | mA |



| TRIGGERING | | | | |
|---|-------------|--|--|--------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES UNITS |
| Maximum peak gate power | P_{GM} | $T_J = T_J$ maximum, $t_p \leq 5$ ms | | 12 W |
| Maximum average gate power | $P_{G(AV)}$ | $T_J = T_J$ maximum, $f = 50$ Hz, $d\% = 50$ | | 3 |
| Maximum peak positive gate current | I_{GM} | $T_J = T_J$ maximum, $t_p \leq 5$ ms | | 3 A |
| Maximum peak positive gate voltage | $+V_{GM}$ | | | 20 V |
| Maximum peak negative gate voltage | $-V_{GM}$ | | | 10 |
| Maximum DC gate current required to trigger | I_{GT} | $T_J = -40$ °C | Maximum required gate trigger/ current/voltage are the lowest value which will trigger all units 6 V anode to cathode applied | 270 mA |
| | | $T_J = 25$ °C | | 120 |
| | | $T_J = 125$ °C | | 60 |
| Maximum DC gate voltage required to trigger | V_{GT} | $T_J = -40$ °C | | 3.5 V |
| | | $T_J = 25$ °C | | 2.5 |
| | | $T_J = 125$ °C | | 1.5 |
| DC gate current not to trigger | I_{GD} | $T_J = T_J$ maximum | Maximum gate current/voltage not to trigger is the maximum value which will not trigger any unit with rated V_{DRM} anode to cathode applied | 6 mA |
| DC gate voltage not to trigger | V_{GD} | | | 0.25 V |

| THERMAL AND MECHANICAL SPECIFICATIONS | | | | |
|--|------------|---|------------------|------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
| Maximum operating junction temperature range | T_J | | - 40 to 125 | °C |
| Maximum storage temperature range | T_{Stg} | | - 40 to 150 | |
| Maximum thermal resistance, junction to case | R_{thJC} | DC operation | 0.30 | K/W |
| Maximum thermal resistance, case to heatsink | R_{thCS} | Mounting surface, smooth, flat and greased | 0.1 | |
| Mounting torque, ± 10 % | | Non-lubricated threads | 15.5 (137) | N · m (lbf · in) |
| | | Lubricated threads | 14 (120) | |
| Approximate weight | | | 130 | g |
| Case style | | See dimensions - link at the end of datasheet | TO-94 (TO-209AC) | |

| ΔR_{thJC} CONDUCTION | | | | |
|------------------------------|-----------------------|------------------------|---------------------|-------|
| CONDUCTION ANGLE | SINUSOIDAL CONDUCTION | RECTANGULAR CONDUCTION | TEST CONDITIONS | UNITS |
| 180° | 0.042 | 0.030 | $T_J = T_J$ maximum | K/W |
| 120° | 0.050 | 0.052 | | |
| 90° | 0.064 | 0.070 | | |
| 60° | 0.095 | 0.100 | | |
| 30° | 0.164 | 0.165 | | |

Note

- The table above shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristics




Fig. 9 - Gate Characteristics

ORDERING INFORMATION TABLE

| Device code | VS- | 8 | 0 | RIA | 120 | M | PbF |
|-------------|-----|---|--|-----|-----|---|-----|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 1 | - | Vishay Semiconductors product | | | | | |
| 2 | - | $I_{TAV} \times 10$ A | | | | | |
| 3 | - | | • 0 = eyelet terminals (gate and auxiliary cathode leads) • 1 = fast-on terminals (gate and auxiliary cathode leads) • 2 = flag terminals (gate and auxiliary cathode terminals) | | | | |
| 4 | - | RIA = essential part number | | | | | |
| 5 | - | Voltage code $\times 100 = V_{RRM}$ (see Voltage Ratings table) | | | | | |
| 6 | - | | • None = stud base 1/2"-20UNF- 2 A threads • M = stud base metric threads M12 x 1.75 E 6 | | | | |
| 7 | - | | None = standard production PbF = lead (Pb)-free | | | | |


LINKS TO RELATED DOCUMENTS

Dimensions

www.vishay.com/doc?95362

TO-209AC (TO-94) for 80RIA Series

DIMENSIONS in millimeters (inches)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.