


## “High Side Chopper” IGBT SOT-227 (Trench IGBT), 47 A


**SOT-227**

### FEATURES

- Trench IGBT technology
- Square RBSOA
- HEXFRED® clamping diode
- Positive  $V_{CE(on)}$  temperature coefficient
- Fully isolated package
- Speed 8 kHz to 60 kHz
- Very low internal inductance ( $\leq 5$  nH typical)
- Industry standard outline
- UL approved file E78996 
- Material categorization: for definitions of compliance please see [www.vishay.com/doc299912](http://www.vishay.com/doc299912)


**RoHS  
COMPLIANT**

### PRIMARY CHARACTERISTICS

$V_{CES}$	1200 V
$I_C$ DC	50 A at 73 °C
$V_{CE(on)}$ typical at 50 A, 25 °C	2.39 V
Package	SOT-227
Circuit configuration	High side chopper

### BENEFITS

- Designed for increased operating efficiency in power conversion: UPS, SMPS, welding, induction heating
- Easy to assemble and parallel
- Direct mounting on heatsink
- Plug-in compatible with other SOT-227 packages
- Low EMI, requires less snubbing

### ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Collector to emitter voltage	$V_{CES}$		1200	V
Continuous collector current	$I_C$	$T_C = 25\text{ °C}$	68	A
		$T_C = 80\text{ °C}$	47	
Pulsed collector current	$I_{CM}$	$T_C = 150\text{ °C}$ , $T_p = 6\text{ ms}$ , $V_{GE} = 15\text{ V}$	150	
Clamped inductive load current	$I_{LM}$		250	
Diode continuous forward current	$I_F$	$T_C = 25\text{ °C}$	87	
		$T_C = 80\text{ °C}$	59	
Single pulse forward current	$I_{FSM}$	10 ms sine or 6 ms rectangular pulse, $T_J = 25\text{ °C}$	310	
Gate to emitter voltage	$V_{GE}$		$\pm 20$	V
Power dissipation, IGBT	$P_D$	$T_C = 25\text{ °C}$	291	W
		$T_C = 80\text{ °C}$	163	
Power dissipation, diode	$P_D$	$T_C = 25\text{ °C}$	338	
		$T_C = 80\text{ °C}$	190	
RMS isolation voltage	$V_{ISOL}$	Any terminal to case, $t = 1\text{ min}$	2500	V

**ELECTRICAL SPECIFICATIONS** ( $T_J = 25\text{ }^{\circ}\text{C}$  unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Collector to emitter breakdown voltage	$V_{BR(CES)}$	$V_{GE} = 0\text{ V}$ , $I_C = 2\text{ mA}$	1200	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	$V_{GE} = 15\text{ V}$ , $I_C = 25\text{ A}$	-	1.95	-	
		$V_{GE} = 15\text{ V}$ , $I_C = 50\text{ A}$	-	2.39	2.8	
		$V_{GE} = 15\text{ V}$ , $I_C = 25\text{ A}$ , $T_J = 125\text{ }^{\circ}\text{C}$	-	2.13	-	
		$V_{GE} = 15\text{ V}$ , $I_C = 50\text{ A}$ , $T_J = 125\text{ }^{\circ}\text{C}$	-	2.76	-	
Gate threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$ , $I_C = 2\text{ mA}$	4.6	5.8	7.6	
Temperature coefficient of threshold voltage	$V_{GE(th)}/\Delta T_J$	$V_{CE} = V_{GE}$ , $I_C = 2\text{ mA}$ ( $25\text{ }^{\circ}\text{C}$ to $125\text{ }^{\circ}\text{C}$ )	-	-13	-	mV/ $^{\circ}\text{C}$
Collector to emitter leakage current	$I_{CES}$	$V_{GE} = 0\text{ V}$ , $V_{CE} = 1200\text{ V}$	-	1.7	50	$\mu\text{A}$
		$V_{GE} = 0\text{ V}$ , $V_{CE} = 1200\text{ V}$ , $T_J = 125\text{ }^{\circ}\text{C}$	-	26.2	-	
Diode reverse breakdown voltage	$V_{BR}$	$I_R = 1\text{ mA}$	1200	-	-	V
Diode forward voltage drop	$V_{FM}$	$I_F = 25\text{ A}$ , $V_{GE} = 0\text{ V}$	-	2.11	2.42	V
		$I_F = 50\text{ A}$ , $V_{GE} = 0\text{ V}$	-	2.72	-	
		$I_F = 25\text{ A}$ , $V_{GE} = 0\text{ V}$ , $T_J = 125\text{ }^{\circ}\text{C}$	-	2.04	-	
		$I_F = 50\text{ A}$ , $V_{GE} = 0\text{ V}$ , $T_J = 125\text{ }^{\circ}\text{C}$	-	2.83	-	
Diode reverse leakage current	$I_{RM}$	$V_R = 1200\text{ V}$	-	4	50	$\mu\text{A}$
		$T_J = 125\text{ }^{\circ}\text{C}$ , $V_R = 1200\text{ V}$	-	0.8	-	mA
Gate to emitter leakage current	$I_{GES}$	$V_{GE} = \pm 20\text{ V}$	-	-	$\pm 200$	nA

**SWITCHING CHARACTERISTICS** ( $T_J = 25\text{ }^{\circ}\text{C}$  unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Total gate charge (turn-on)	$Q_g$	$I_C = 40\text{ A}$ , $V_{CC} = 960\text{ V}$ , $V_{GE} = 15\text{ V}$	-	171	-	nC
Gate to emitter charge (turn-on)	$Q_{ge}$		-	22	-	
Gate to collector charge (turn-on)	$Q_{gc}$		-	86	-	
Turn-on switching loss	$E_{on}$	$I_C = 50\text{ A}$ , $V_{CC} = 600\text{ V}$ , $V_{GE} = 15\text{ V}$ , $R_g = 4.7\text{ }\Omega$ , $L = 500\text{ }\mu\text{H}$ , $T_J = 25\text{ }^{\circ}\text{C}$	-	2.7	-	mJ
Turn-off switching loss	$E_{off}$		-	1.4	-	
Total switching loss	$E_{tot}$		-	4.1	-	
Turn-on switching loss	$E_{on}$		-	4.1	-	
Turn-off switching loss	$E_{off}$		-	2.3	-	
Total switching loss	$E_{tot}$		-	6.4	-	
Turn-on delay time	$t_{d(on)}$		-	8	-	ns
Rise time	$t_r$		-	11	-	
Turn-off delay time	$t_{d(off)}$		-	81	-	
Fall time	$t_f$		-	179	-	
Reverse bias safe operating area	RBSOA	$T_J = 150\text{ }^{\circ}\text{C}$ , $I_C = 250\text{ A}$ , $R_g = 4.7\text{ }\Omega$ , $V_{GE} = 15\text{ V}$ to $0\text{ V}$ , $V_{CC} = 700\text{ V}$ , $V_P = 1200\text{ V}$	Fullsquare			
Diode reverse recovery time	$t_{rr}$	$I_F = 50\text{ A}$ , $dI_F/dt = 200\text{ A}/\mu\text{s}$ , $V_R = 200\text{ V}$	-	129	-	ns
Diode peak reverse current	$I_{rr}$		-	11	-	A
Diode recovery charge	$Q_{rr}$		-	710	-	nC
Diode reverse recovery time	$t_{rr}$	$I_F = 50\text{ A}$ , $dI_F/dt = 200\text{ A}/\mu\text{s}$ , $V_R = 200\text{ V}$ , $T_J = 125\text{ }^{\circ}\text{C}$	-	208	-	ns
Diode peak reverse current	$I_{rr}$		-	17	-	A
Diode recovery charge	$Q_{rr}$		-	1768	-	nC

THERMAL AND MECHANICAL SPECIFICATIONS						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Junction and storage temperature range	$T_J, T_{Stg}$		-40	-	150	°C
Junction to case	$R_{thJC}$	IGBT	-	-	0.43	°C/W
			-	-	0.37	
Case to heatsink	$R_{thCS}$	Flat, greased surface	-	0.05	-	
Weight			-	30	-	g
Mounting torque		Torque to terminal	-	-	1.1 (9.7)	Nm (lbf.in)
		Torque to heatsink	-	-	1.8 (15.9)	Nm (lbf.in)
Case style	SOT-227					




Fig. 1 - Typical Trench IGBT Output Characteristics,  $V_{GE} = 15 \text{ V}$ 


Fig. 3 - Maximum Trench IGBT Continuous Collector Current vs. Case Temperature




Fig. 2 - Typical Trench IGBT Output Characteristics,  $T_J = 125 \text{ °C}$ 


Fig. 4 - Typical Trench IGBT Transfer Characteristic




Fig. 5 - Typical Trench IGBT Gate Threshold Voltage







Fig. 8 - Typical Trench IGBT Switching Time vs.  $I_C$   
 $T_J = 125\text{ }^{\circ}\text{C}$ ,  $V_{CC} = 600\text{ V}$ ,  $R_g = 4.7\text{ }\Omega$ ,  $V_{GE} = +15\text{ V}/-15\text{ V}$ ,  $L = 500\text{ }\mu\text{H}$ 


Fig. 6 - Typical Trench IGBT Zero Gate Voltage Collector Current


Fig. 9 - Typical Trench IGBT Energy Losses vs.  $R_g$   
 $T_J = 125\text{ }^{\circ}\text{C}$ ,  $V_{CC} = 600\text{ V}$ ,  $I_C = 50\text{ A}$ ,  $V_{GE} = +15\text{ V}/-15\text{ V}$ ,  $L = 500\text{ }\mu\text{H}$ 

Fig. 7 - Typical Trench IGBT Energy Loss vs.  $I_C$   
 $T_J = 125\text{ }^{\circ}\text{C}$ ,  $V_{CC} = 600\text{ V}$ ,  $R_g = 4.7\text{ }\Omega$ ,  $V_{GE} = +15\text{ V}/-15\text{ V}$ ,  $L = 500\text{ }\mu\text{H}$ 

Fig. 10 - Typical Trench IGBT Switching Time vs.  $R_g$   
 $T_J = 125\text{ }^{\circ}\text{C}$ ,  $V_{CC} = 600\text{ V}$ ,  $I_C = 50\text{ A}$ ,  $V_{GE} = +15\text{ V}/-15\text{ V}$ ,  $L = 500\text{ }\mu\text{H}$




Fig. 11 - Typical Trench IGBT Gate Charge vs. Gate to Emitter Voltage




Fig. 14 - Typical Diode Reverse Recovery Time vs.  $dI_F/dt$




Fig. 12 - Typical Diode Forward Characteristic




Fig. 15 - Typical Diode Reverse Recovery Current vs.  $dI_F/dt$




Fig. 13 - Maximum Diode Continuous Forward Current vs. Case Temperature




Fig. 16 - Typical Diode Reverse Recovery Charge vs.  $dI_F/dt$




Fig. 17 - Trench IGBT Reverse BIAS SOA  
 $T_J = 150^\circ\text{C}$ ,  $I_C = 250\text{ A}$ ,  $R_g = 4.7\ \Omega$ ,  $V_{GE} = +15\text{ V}/0\text{ V}$ ,  
 $V_{CC} = 700\text{ V}$ ,  $V_p = 1200\text{ V}$




Fig. 18 - Trench IGBT Safe Operating Area




Fig. 19 - Maximum Trench IGBT Thermal Impedance  $Z_{thJC}$  Characteristics





Fig. 20 - Maximum Diode Thermal Impedance  $Z_{thJC}$  Characteristics



ORDERING INFORMATION TABLE

Device code	VS-	G	T	55	N	A	120	U	X
	1	2	3	4	5	6	7	8	9


- |   |   |                                               |
|---|---|-----------------------------------------------|
| 1 | - | Vishay Semiconductors product                 |
| 2 | - | Insulated gate bipolar transistor (IGBT)      |
| 3 | - | T = trench IGBT                               |
| 4 | - | Current rating (55 = 55 A)                    |
| 5 | - | Circuit configuration (N = high side chopper) |
| 6 | - | Package indicator (A = SOT-227)               |
| 7 | - | Voltage rating (120 = 1200 V)                 |
| 8 | - | Speed/type (U = ultrafast IGBT)               |
| 9 | - | Diode (X = HEXFRED® diode)                    |

CIRCUIT CONFIGURATION		
CIRCUIT	CIRCUIT CONFIGURATION CODE	CIRCUIT DRAWING
High side chopper	N	

LINKS TO RELATED DOCUMENTS	
Dimensions	<a href="http://www.vishay.com/doc?95423">www.vishay.com/doc?95423</a>
Packaging information	<a href="http://www.vishay.com/doc?95425">www.vishay.com/doc?95425</a>

## SOT-227 Generation 2

**DIMENSIONS** in millimeters (inches)



### Note

- Controlling dimension: millimeter





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.