



The DNA of tech.™



Multi-Anode Solid Tantalum Capacitors for High Capacitance and Rated Voltages Up to 75 V

Vishay offers leading-edge solid tantalum chip capacitors that combine a multi-anode conformal coated construction with high capacitance / voltage (CV) ratings in a single package for all power supplies and power distribution. Available devices include the commercial 597D series and the Hi-Rel COTS T97, which includes failure rate levels and surge current options and is approved to DLA Drawing 13008. The devices are ideal for use in industrial equipment, civil avionic and defense, space, and communications markets.

Industry standards and established design guidelines typically require voltage derating in solid tantalum capacitors to 50 % of the rated voltage. Vishay's multi-anode solid tantalum devices offer high voltage ratings of 63 V and 75 V, which meet the MIL-STD-704 specification for +28 V buses in aircraft electric power systems.

Additional Key Advantages

- Leading-edge ratings
 - 680 μF / 16 V, 470 μF / 20 V, 220 μF / 25 V
 - 100 μF / 40 V, 47 μF / 50 V, 33 μF / 63 V, 22 μF / 75 V
- Ultra low DCL down to 8 μA
- Low ESR down to 0.018 Ω
- Weibull failure rates A, B, and C available
- Surge current testing per MIL-PRF-55365

Useful Links

- 597D Product Page www.vishay.com/ppg?40047
- T97 Product Page www.vishay.com/ppg?40092
- 13008 Product Page www.vishay.com/ppg?40164
- Tantalum Parametric Search www.vishay.com/capacitors/tantalum/
- Technical Note: Voltage Derating www.vishay.com/doc?40246

Contact Information

The Americas

David Bellomy
David.Bellomy@vishay.com

Europe

Thomas Poessnecker
Thomas.Poessnecker@vishay.com

Asia / Pacific

BH Tan
Boonhooi.Tan@vishay.com